

Tekniske data

2627-H | Spare Sensor Kit with High-Accuracy Sensor





Produktoversigt: 2627-H | Spare Sensor Kit with High-Accuracy Sensor

One of the potential advantages of a digital thermo-hygrometer is that instead of sending the entire unit out for calibration, you can simply swap sensors and send only the sensors due for calibration out of the lab. The 1620A "DewK" Thermo-Hygrometer allows you to swap sensors without shutting it down or discontinuing your other readings.

Smart sensors make this possible because all of the calibration information is contained inside the sensor. Your costs are reduced because the 1620A never needs to be calibrated since it is only a display. Spare sensors like the 2627-H are less expensive to store, ship and recalibrate than an extra chart recorder.

With each kit you get a:

- High-accuracy sensor
- Sensor wall mount bracket
- 7.6 m (25 ft) extension cable

Modeller



2627-H

Spare Sensor Kit with High-Accuracy Sensor

Fluke. *Keeping your world up and running.®*

Fluke Danmark A/S
c/o Radiometer Medical ApS
Åkandevvej 21
2700 Brønshøj
Danmark
Tlf.: 70 23 58 53
E-mail: cs.dk@fluke.com
www.fluke.dk

©2025 Fluke Corporation. Alle rettigheder
forbeholdes.
Oplysningerne kan ændres uden forudgående
varsel.
04/2025

**Ændringer i dette dokument er ikke tilladt uden
skriftlig tilladelse fra Fluke Corporation.**