

Technische daten

9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well



Produktübersicht: 9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well

9190A Carrying Case

- Carrying case for the 9190A Ultra-Cool Field Metrology Well
- Dent- and shatter-resistant strong resin case
- Foam lined for impact protection
- Handle and wheels for easy transporting

Technische Daten: 9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well

Dimensions

Exterior: (L x W x D) 24.90 in x 23.70 in x 13.10 in (63.25 cm x 60.2 cm x 33.27 cm)

Interior: (L x W x D) 22.50 in x 21.10 in x 11.40 in (57.15 cm x 53.59 cm x 28.96 cm)

Weight

With foam: 27 lbs (12.25 kg)

Without foam: 20.1 lbs (9.12 kg)

Temperature rating

-10 °F to +210 °F (-23 °C to +99 °C)

Modelle



9190-CASE

Carrying Case, 9190A Ultra-Cool Field Metrology Well

Fluke. *Damit Ihre Welt intakt bleibt.*

Fluke (Switzerland) GmbH

Industrial Division
Hardstrasse 20
CH-8303 Bassersdorf
Telefon: +41 (0) 44 580 7504
E-Mail: info@ch.fluke.nl
www.fluke.ch

©2025 Fluke Corporation. Alle Rechte vorbehalten.
Anderungen vorbehalten
04/2025

**Dieses Dokument darf nicht ohne die schriftliche
Genehmigung der Fluke Corporation geändert
werden.**

Technischer Beratung:

Beratung zu Produkteigenschaften, Spezifikationen,
Messgeräte und Anwendungsfragen
Tel.: +49 (0) 7684 8 00 95 45
E-Mail: techsupport.dach@fluke.com