

TECHNICAL DATA

9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well



Product overview: 9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well

9190A Carrying Case

- Carrying case for the 9190A Ultra-Cool Field Metrology Well
- Dent- and shatter-resistant strong resin case
- Foam lined for impact protection
- Handle and wheels for easy transporting

Specifications: 9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well

Dimensions

Exterior: (L x W x D) 24.90 in x 23.70 in x 13.10 in (63.25 cm x 60.2 cm x 33.27 cm)

Interior: (L x W x D) 22.50 in x 21.10 in x 11.40 in (57.15 cm x 53.59 cm x 28.96 cm)

Weight

With foam: 27 lbs (12.25 kg)

Without foam: 20.1 lbs (9.12 kg)

Temperature rating

-10 °F to +210 °F (-23 °C to +99 °C)

Ordering information



9190-CASE

Carrying Case, 9190A Ultra-Cool Field Metrology Well



Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

Fluke Australia
Unit 26, 7 Anella Ave
Castle Hill, NSW 2154 Australia
Phone: 61 2 8850-3333
www.fluke.com.au

©2025 Fluke Corporation. All rights reserved.
Specifications subject to change without notice.
03/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**