

TECHNICAL DATA

3140-3 | Insert, 9140 "B" w/ cmprsn hls, ring



Product overview: 3140-3 | Insert, 9140 "B" w/ cmprsn hls, ring

Removable inserts are sized for probes with the named diameter. Use additional inserts to broaden the range of hole sizes available or to back up or replace existing inserts. This insert is designed for use with the 9140 Field Dry-Well.

- Insert "B" 9140
- Holes: ¼ in (2); 3/8 in (2); 3/16 in (2)

Specifications: 3140-3 | Insert, 9140 "B" w/ cmprsn hls, ring

Hole size	Quantity
4.8 mm (3/16 in)	2
6.35 mm (1/4 in)	2
9.5 mm (3/8 in)	2

Ordering information

**3140-3**

Insert, 9140 "B" w/ cmprsn hls, ring



Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2025 Fluke Corporation.
Specifications subject to change without notice.
03/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**