

TECHNICAL DATA

Fluke 700PRV Pressure Relief Valve Kit



Key features

Repeatability \pm 10% of nominal setting. Multi-turn adjustment screw to set preload on internal disc springs.

Included:

- The 700PRV contains two relief valves
 - One adjustable from 725-2900 psi/50-200 bar (preset at 1360 psi/94 bar)
 - One adjustable from 2900-5800 psi/200-400 bar (preset at 5450 psi/376 bar)
- Instruction sheet

Product overview: Fluke 700PRV Pressure Relief Valve Kit

The Fluke 700PRV consists of two relief valves (1360 and 5450 psi) to be used with the 700HTP Hydraulic Test Pump. These relief valves will protect the most commonly used Fluke pressure modules from damage due to accidental over-pressurization. 1/4 BSP male parallel thread to fit Fluke 700HTP.

Specifications: Fluke 700PRV Pressure Relief Valve Kit

Size	40 x 22 mm
Weight	60 g per relief valve
Warranty	One year
Material	Type 303 stainless steel

Ordering information



Fluke 700PRV

Fluke 700PRV Pressure Relief Valve Kit



Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2025 Fluke Corporation.
Specifications subject to change without notice.
04/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**