

TECHNICAL DATA

PLS 3G KIT, 3-Point Green Laser Kit







Key features

- Accuracy: $\pm 1/8$ in at 30 ft. (± 3 mm @ 10 m)
- Green beam laser level
- Point laser direction: 90° up, down, forward
- Durable pendulum lock platform.
- IP54 rating to limit dust and water entry for years of operation on the job site.

Product overview: PLS 3G KIT, 3-Point Green Laser Kit

The new PLS 3G green laser levels offer the durability and precision you expect from PLS, a Fluke Company. Our new laser level platform offers a pendulum lock platform for safe transport and tilt mode functionality. The fast settling, self-leveling pendulum gives you accurate point and reference lines almost instantly.

- This professional self-leveling three-point red and green laser level allows for fast, accurate layout of reference points and is excellent for steel stud framing, HVAC installation, electrical and residential construction
- The PLS 3G green beam laser is up to three times brighter than the PLS 3R red beam, making it ideal for projects over longer distances or with lower lighting.
- Kit includes floor stand and L-bracket for fast, easy overhang and centerline measurements.

Specifications: PLS 3G KIT, 3-Point Green Laser Kit

PLS 3G

Baery	3 x AA Alkaline IEC LR6	
Baery Life, Continuous Use	Red	□ 30 hours
	Green	□ 16 hours
Point Laser Direction	90° up, down, forward	
Working Range	□ 30 m (100 ft.)	
Accuracy	□ 3 mm @ 10 m (□ 1/8 in at 30 ft.)	
Laser Leveling	System	Automatic, Pendulum
	Range	4 °
Point Laser Diameter	□ 4 mm at 5 m	
Temperature	Operating	-10 °C to 50 °C (14 °F to 122 °F)
	Storage	15 cm x 9 cm x 3 cm (6 in x 3.6 in x 1.3 in)
	With Baeries	-18 °C to 50 °C (-0.4 °F to 122 °F)
	Without Baeries	-20 °C to 70 °C (-13 °F to 158 °F)
Relative Humidity	0 % to 90 % (0 °C to 35 °C)	
	0 % to 75 % (35 °C to 40 °C)	
	0 % to 45 % (40 °C to 50 °C)	
Size (H x W X L)	116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in)	
Weight	~0.6 kg (1.3 lb.)	
Safety	IEC 61010-1: Pollution Degree 2	
Laser	IEC 60825-1:2014 Class 2	
Light Source	Semiconductor laser diode	
Max Output Power	< 1 mW	
Wavelength	Red	635 nm ± 5 nm
	Green	525 nm ± 5 nm

Electromagnetic Compatibility (EMC)

Inteational
Korea (KCC)
USA (FCC)

Fluke. *Keeping your world up and running.®*

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:

In the U.S.A. (800) 443-5853

In Canada (800) 36-FLUKE

From other countries +1 (425) 446-5500

www.fluke.com

©2025 Fluke Corporation.

Specifications subject to change without notice.

03/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**