

Fluke 700P22 Differential Pressure Module Wet



Key features

- Rugged urethane molded case protects the module from rough handling and harsh conditions
- Features internal temperature compensation from 0 °C to 50 °C for full-accuracy performance
- Includes NIST-traceable calibration certificate
- Module can be calibrated locally using the Fluke 700PCK Pressure Calibration Kit, a PC, and a precision pressure source
- One year warranty

Product overview: Fluke 700P22 Differential Pressure Module Wet

Display pressure readings in any of 10 different pressure units you specify in the calibrator setup

Specifications: Fluke 700P22 Differential Pressure Module Wet

Specifications	
Range	1 psi / 6900 Pa
Resolution	0.0001 / 0.7

Reference Uncertainty (23 ± 3°C)	0.100%
Total ¹ Uncertainty 1 year	0.150
High Side Media ²	316 SS
Low Side Media ²	Dry
<p>1. Total uncertainty, one year for temperature range 0°C to +50°C. Total uncertainty, 1.0% of full span for temperature range -10°C to 0°C. Compensated temperature range is 15°C to 35°C.</p> <p>2. "Dry" indicates dry air or non-corrosive gas as compatible media. "316 SS" indicates media compatible with Type 316 Stainless Steel. "C276" indicates media compatible with Hastelloy C276.</p>	

Ordering information



Fluke 700P22

Differential Pressure Module Wet

Fluke 700P22 Differential Pressure Module Wet

Fluke. *Keeping your world up and running.®*

Fluke (UK) Ltd.
52 Hurricane Way
Norwich, Norfolk
NR6 6JB
United Kingdom
Tel.: +44 (0)20 7942 0708
E-mail: cs.uk@fluke.com
www.fluke.com/en-gb

©2025 Fluke Corporation. All rights reserved.
Data subject to alteration without notice.
04/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**