

TECHNICAL DATA

# Fluke VPS250 2.5 m Voltage Probe Set 75 MHz



## Key features

### Product overview: Fluke VPS250 2.5 m Voltage Probe Set 75 MHz

Double insulated voltage probe

### Specifications: Fluke VPS250 2.5 m Voltage Probe Set 75 MHz

General Specifications	
Aenuation	10x
Bandwidth	75 MHz
Max. input voltage	1000 V
Max. voltage to ground	600 V CAT III, 1000 V CAT II per IEC / EN61010-31
Input resistance	10 Mohm
Input capacitance	18.5 pF



Compensation range	10 to 35 pF
Cable Length	2.5 m
BB120 Shielded Banana to BNC Adapter is required to adapt to ScopeMeter 120 Series shielded banana jack inputs.	

## Ordering information



### Fluke VPS250

2.5 m Voltage Probe Set 75 MHz

---

Each probe set includes:

- 600 V CAT III / 1000 V CAT II rated
  - 10:1 Voltage probe
  - Hook clip for probe tip, 4-mm test probe for probe
  - Ground lead with hook clip
  - Ground lead with mini alligator
  - One year warranty
-

**Fluke.** *Keeping your world up and running.®*

**Fluke (UK) Ltd.**  
52 Hurricane Way  
Norwich, Norfolk  
NR6 6JB  
United Kingdom  
Tel.: +44 (0)20 7942 0708  
E-mail: [cs.uk@fluke.com](mailto:cs.uk@fluke.com)  
[www.fluke.com/en-gb](http://www.fluke.com/en-gb)

©2025 Fluke Corporation. All rights reserved.  
Data subject to alteration without notice.  
04/2025

**Modification of this document is not permitted  
without written permission from Fluke  
Corporation.**