

TECHNICAL DATA

5520A-525A/LEADS |Test Lead Set



Product overview: 5520A-525A/LEADS |Test Lead Set

Designed for use on the 5522A Multi-Product Calibrator; also suitable for the 525B and 7526A Temperature/Pressure Calibrators

The 5520A-525A/LEADS are professional-quality lead sets that ensure you always have the right probes and connectors for the job at hand. These top quality leads provide years of service and are designed to minimize connection loss and thermal effects. Each test lead has silicon insulation for easy handling and is rated at 1000V. In addition to the test leads, each Fluke Calibration lead set contains a full set of thermocouple extension wires with mini-thermocouple connectors on each end for fast, trouble-free calibration of thermocouple instruments. Each Fluke Calibration lead set convenient transporting and storage.

This lead set is ideally suited for the 5522A Multi-Product Calibrator. It includes all thermocouple type extensions used on the 5522A, terminated with male-to-male mini-connectors on both ends for easy calibration hookups. This lead set is also suitable for the 525B and 7526A Temperature/Pressure Calibrators and the earlier 5520A Multi-Product



Calibrators.

Parts included in the 5520A-525A/LEADS test lead set

Quantity	Description
1	Soft case 6.5" x 11" x 2.5" (16.51 x 27.94 x 6.35 cm)
1	T/C assembly, K-Type, beaded, molded plug
1	T/C assembly, J-Type, beaded, molded plug
1	T/C, molded-plug, copper shorting
1	Thermocouple adapter, K mini T/C to banana (80AK)
1	Thermocouple extension, 3 feet (1M), B
1	Thermocouple extension, 3 feet (1M), E
1	Thermocouple extension, 3 feet (1M), J
1	Thermocouple extension, 3 feet (1M), K
1	Thermocouple extension, 3 feet (1M), N
1	Thermocouple extension, 3 feet (1M), R
1	Thermocouple extension, 3 feet (1M), S
1	Thermocouple extension, 3 feet (1M), CU
1	Thermocouple extension, 3 feet (1M), T
2	Dual binding post adapters, banana plug
2	High current, 30A, test lead
2	Shielded calibration test leads, 24", banana plug

One-year warranty Test leads

- Category I, rated 1000V
- Rated current, 10A

Thermocouple extensions

- 16 Ga
- PTFE jacket
- Standard limits of error



Ordering information



5520A-525A/LEADS

Test Lead Set



Fluke. Keeping your world up and running.®

Fluke (UK) Ltd. 52 Hurricane Way Norwich, Norfolk NR6 6JB United Kingdom Tel.: +44 (0)20 7942 0708 E-mail: cs.uk@fluke.com www.fluke.com/en-gb ©2025 Fluke Corporation. All rights reserved. Data subject to alteration without notice. 03/2025

Modification of this document is not permitted without written permission from Fluke Corporation.