

TECHNICAL DATA

# Fluke AC280 SureGrip™ Hook Clips



## Key features

- One pair of nickel-plated clips (red, black) with a profile narrowing to 5.6 mm at the tip and a hook opening of 6.4 mm at the front, reducing to 2 mm at the base
- Provides reliable and secure connections for precise electrical measurements
- Rated CAT II 1000 V, CAT III 1000 V, CAT IV 600 V, 3 A
- Recommended for use with TL222 and TL224 test leads

## Product overview: Fluke AC280 SureGrip™ Hook Clips

SureGrip™ accessories are designed to improve steadiness in slippery hands. Rubber overmolded surfaces and finger-hugging curves give the user a comfortable, reliable grip on the accessory so they can focus on making an accurate measurement.

## Ordering information



### **Fluke AC280**

Fluke AC280 SureGrip™ Hook Clips

---

**Fluke.** *Keeping your world up and running.®*

**Fluke (UK) Ltd.**  
52 Hurricane Way  
Norwich, Norfolk  
NR6 6JB  
United Kingdom  
Tel.: +44 (0)20 7942 0708  
E-mail: [cs.uk@fluke.com](mailto:cs.uk@fluke.com)  
[www.fluke.com/en-gb](http://www.fluke.com/en-gb)

©2025 Fluke Corporation. All rights reserved.  
Data subject to alteration without notice.  
03/2025

**Modification of this document is not permitted  
without written permission from Fluke  
Corporation.**