

## TECHNICAL DATA

# Fluke 700PRV-1 Pressure Relief Valve Kit



## Key features

- Adjustable from 725 to 5800 PSI (50 to 200 bar)
- Preset at 2,900 psi/200 bar
- Repeatability to 10% of nominal setting
- Installs directly into the 700HTP-1 pump

## Product overview: Fluke 700PRV-1 Pressure Relief Valve Kit

The Fluke 700PRV-1 consists of a relief valve settable from 725 to 5800 PSI (50 to 200 bar) to be used with the 700HTP-1 Hydraulic Test Pump. The 1/8" NPT male thread to fits directly into the Fluke 700HTP-1 pressure pump.

To be used with the 700HTP-1 Hydraulic Test Pump. The 700PRV uses a multi-turn adjustment screw to set preload on internal disc springs. This relief valve will protect the most commonly used Fluke pressure modules and pressure instruments from damage due to accidental over-pressurization.

## Specifications: Fluke 700PRV-1 Pressure Relief Valve Kit

### Mechanical and General Specifications

Size	1.52 in by 0.62 in diameter (38 mm by 16 mm diameter)
------	---

Weight	1.6 oz (46 g)
Warranty	One year
Material	Type 303 stainless steel

## Ordering information



### **Fluke 700PRV-1**

Fluke 700PRV-1 Pressure Relief Valve Kit

- 
- One adjustable relief valve
  - Instruction sheet
-

**Fluke.** *Keeping your world up and running.®*

**Fluke (UK) Ltd.**  
52 Hurricane Way  
Norwich, Norfolk  
NR6 6JB  
United Kingdom  
Tel.: +44 (0)20 7942 0708  
E-mail: [cs.uk@fluke.com](mailto:cs.uk@fluke.com)  
[www.fluke.com/en-gb](http://www.fluke.com/en-gb)

©2025 Fluke Corporation. All rights reserved.  
Data subject to alteration without notice.  
04/2025

**Modification of this document is not permitted  
without written permission from Fluke  
Corporation.**