

TECHNICAL DATA

Fluke Calibration P5521 and P5522 Liquid-to-Liquid Separators



Key features

- P5521-For pressures to 10,000 psi (700 bar)
- P5522-For pressures to 7,000 psi (480 bar) for Skydrol or other aggressive fluids

Product overview: Fluke Calibration P5521 and P5522 Liquid-to-Liquid Separators

These liquid-to-liquid separators connect directly to the test port of a hydraulic deadweight tester or comparison test pump. A flexible diaphragm separates the fluids, protecting the calibrator from contamination, and allows calibration of the device in its specific working fluid.

Specifications: Fluke Calibration P5521 and P5522 Liquid-to-Liquid Separators

Pressure Range	5521: 0 to 10,000 psi (700 bar) 5522: 0 to 7,000 psi (480 bar) for Skydrol and other aggressive fluids
Instrument Size (W x H)	4 x 6 in (100 x 150 mm)
Instrument Weight	7.5 lb (3.5 kg)
Test Port Adapter	Uses adapters supplied with calibrator
Calibrator Connection	3/8 BSP male (mating adapter supplied)
Body Material	Aluminum bronze
Diaphragm	5521- Viton® 5522-Ethylene Propylene
Reservoir Material	Hard-anodized aluminum

Ordering information

**P5521**

P5521 Liquid to Liquid Separators
Pressure Range 0 to 10,000 psi (700 bar)

P5522

P5522 Liquid-to-Liquid Separator
Pressure Range 0 to 7,000 psi (480 bar)

Fluke. *Keeping your world up and running.®*

Fluke (UK) Ltd.
52 Hurricane Way
Norwich, Norfolk
NR6 6JB
United Kingdom
Tel.: +44 (0)20 7942 0708
E-mail: cs.uk@fluke.com
www.fluke.com/en-gb

©2025 Fluke Corporation. All rights reserved.
Data subject to alteration without notice.
03/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**