

## TECHNICAL DATA

# 7009/7108/7015 Resistor Baths



## Key features

- Three size options to accommodate any quantity of resistors.
- High temperature stability to  $\pm 0.0007$  °C.
- Includes independent high- and low-temperature cutout circuit.
- Minimizes long-term drift for consistent performance.
- Proprietary controller that senses temperature changes as small as  $0.00001$  °C, improving stability.

## Product overview: 7009/7108/7015 Resistor Baths

### 7015

The 7015 has a 95-liter tank and a temperature range of 0 °C to 50 °C. It's stable to  $\pm 0.0007$  °C.

It has a one-piece stainless steel lid designed to drain spills and splashes back into the bath as you remove resistors. It has a large access opening to make handling large resistors, like the Thomas design standard resistors, easier. The tank has an electrically isolated resistor shelf.

This is truly a quality resistor bath, and it's backed by our industry-leading service.

### 7009

This is a large bath with a tank 27½ inches long by 22 inches wide. It has a temperature range of 0 °C to 50 °C and a

stability of  $\pm 0.0007\text{ }^{\circ}\text{C}$ .

For a bath this size and with these specs, it is priced extremely well. The Model 7009's large tank can handle many resistors of any size.

## 7108

This is the quietest resistor bath you've ever heard. The 7108 uses thermoelectric (Peltier) modules to provide heating and cooling over its range from  $20\text{ }^{\circ}\text{C}$  to  $30\text{ }^{\circ}\text{C}$ . Without a compressor, noise is dramatically reduced. Power requirements are also lower, so you save money running the bath and add less heat load to your lab.

With a 51-liter (13.2-gal) tank, the 7108 holds plenty of resistors. A large 14" x 14" (356 x 356 mm) access opening allows you to easily move resistors in and out of the bath. A resistor rack comes with each unit that fits across the bottom of the tank. Made from hard-anodized perforated aluminum, this rack maintains the necessary electrical isolation between your resistors.

## Specifications: 7009/7108/7015 Resistor Baths

Specifications	7015	7009	7108
<b>Range</b>	$0\text{ }^{\circ}\text{C}$ to $50\text{ }^{\circ}\text{C}^{\dagger}$	$0\text{ }^{\circ}\text{C}$ to $50\text{ }^{\circ}\text{C}^{\dagger}$	$20\text{ }^{\circ}\text{C}$ to $30\text{ }^{\circ}\text{C}$
<b>Stability at <math>25\text{ }^{\circ}\text{C}</math></b>	$\pm 0.0007\text{ }^{\circ}\text{C}$ (water) $\pm 0.001\text{ }^{\circ}\text{C}$ (mineral oil 5011)		$\pm 0.002\text{ }^{\circ}\text{C}$ (water) $\pm 0.004\text{ }^{\circ}\text{C}$ (mineral oil 5011)
<b>Uniformity</b>	$\pm 0.003\text{ }^{\circ}\text{C}$ at $25\text{ }^{\circ}\text{C}$ (water) $\pm 0.005\text{ }^{\circ}\text{C}$ at $25\text{ }^{\circ}\text{C}$ (mineral oil 5011)		$\pm 0.005\text{ }^{\circ}\text{C}$ (water) $\pm 0.008\text{ }^{\circ}\text{C}$ (mineral oil 5011)
<b>Temperature Seing</b>	Digital display with push-buon data ey		
<b>Set-Point Resolution</b>	$0.002\text{ }^{\circ}\text{C}$ ; high-resolution mode, $0.00003\text{ }^{\circ}\text{C}$		
<b>Display Resolution</b>	$0.01\text{ }^{\circ}\text{C}$		
<b>Digital Seing Accuracy</b>	$\pm 1\text{ }^{\circ}\text{C}$		$\pm 0.5\text{ }^{\circ}\text{C}$
<b>Digital Seing Repeatability</b>	$\pm 0.01\text{ }^{\circ}\text{C}$		
<b>Heaters</b>	500 and 1000 Was		Peltier heating/cooling
<b>Cooling Capacity</b>	100 to 200 Was		100 W in ambient $23\text{ }^{\circ}\text{C}$
<b>Access Opening</b>	699 x 279 mm (27.5 x 11 in)	699 x 559 mm (27.5 x 22 in)	356 x 356 mm (14 x 14 in)
<b>Bath Chamber Dimensions (HxWxD) (unobstructed space)</b>	699 x 279 x 330 mm (27.5 x 11 x 13 in)	669 x 559 x 330 mm (27.5 x 22 x 13 in)	356 x 203 x 355 mm (14 x 8 x 14 in)
<b>Depth</b>	330 mm (13 in)		203 mm (8 in)
<b>Weed Parts</b>	304 stainless steel		Tank: 304 stainless steel Resistor rack: hard-anodized, perforated aluminum
<b>Safety Cutout</b>	Factory-set high temperature		n/a

<b>Power</b>	115 VAC ( $\pm 10\%$ ), 60 Hz, 15 A or 230 VAC, 50 or 60 Hz, 8 A, specify	230 VAC ( $\pm 10\%$ ), 50 or 60 Hz, 12 A (specify frequency)	115 VAC ( $\pm 10\%$ ), 50/60 Hz, 3 A or 230 VAC ( $\pm 10\%$ ), 50/60 Hz, 1.6 A, specify
<b>Volume</b>	95 liters (25 gallons)	167 liters (44 gallons)	51 liters (13.2 gallons)
<b>Weight</b>	141 kg (310 lb.)	150 kg (330 lb.)	35 kg (75 lb.)
<b>Size (HxWxD)</b>	1219 x 1118 x 559 mm (48 x 44 x 22 in)	1092 x 1130 x 864 mm (43 x 44.5 x 34 in)	489 x 413 x 559 mm (19.25 x 22 x 25 in)
<b>Automation</b>	Use the 1586A Super-DAQ to automate temperature sensor calibration		

<sup>†</sup>Although the 7015 and 7009 baths are capable of reaching higher temperatures, they are designed for use with standard resistors. Therefore, the soft cutout of the instrument has been set at the factory to 50°C to protect standard resistors placed in the bath.

## Ordering information



### **7015**

Resistor Bath

---

### **7009**

Resistor Bath, high capacity

---

### **7108**

Resistor Bath, Peltier-cooled, includes RS-232

---

### **2001-IEEE**

IEEE-488 Interface, 6330/7320/7340

---

**Fluke.** *Keeping your world up and running.®*

**Fluke (UK) Ltd.**  
52 Hurricane Way  
Norwich, Norfolk  
NR6 6JB  
United Kingdom  
Tel.: +44 (0)20 7942 0708  
E-mail: [cs.uk@fluke.com](mailto:cs.uk@fluke.com)  
[www.fluke.com/en-gb](http://www.fluke.com/en-gb)

©2025 Fluke Corporation. All rights reserved.  
Data subject to alteration without notice.  
03/2025

**Modification of this document is not permitted  
without written permission from Fluke  
Corporation.**