

TECHNICAL DATA

55XXA/DMMCAL | DMM Autocal Adapter







Product overview: 55XXA/DMMCAL | DMM Autocal Adapter

The 55XXA/DMMCAL AUTOCAL ADAPTER is a lead set that connects to the 5560A, 5550A or 5540A Multi-Product Calibrators' output blocks at one end and to a device under test (DUT) on the other. The adapter minimizes manual lead connections during the verification process.

Specifications: 55XXA/DMMCAL | DMM Autocal Adapter

DMM Input/Sense coax cables: 1020 Vrms max
 LO I Current: 3.2 A max



HI I Current: 15 A max

Ordering information



55XXA/DMMCAL

DMM Autocal Adapter

Fluke. *Keeping your world up and running.®*

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:

In the U.S.A. (800) 443-5853

In Europe/M-East/Africa

+31 (0)40 267 5100

In Canada (800)-36-FLUKE

From other countries +1 (425) 446-5500

BUT. FLUKE SOUTH EAST ASIA PTE LTD

Menera Satu Sentra Kelapa Gading #06-05

Jl. Bulevar Kelapa Gading Kav. LA# No. 1

Summarecon Kelapa Gading

Jakarta Utara 14240

Indonesia

Tel: +62 21 2938 5922

Email: info.asean@fluke.com

www.fluke.com/id-en

©2025 Fluke Corporation. Specifications subject to change without notice.

04/2025

Modification of this document is not permitted without written permission from Fluke Corporation.