

TECHNICAL DATA

Fluke i17XX-flex6000 iFlex® Current Clamp



Product overview: Fluke i17XX-flex6000 iFlex® Current Clamp

The Fluke 17XX 36 inch iFlex flexible current probes expand the measurement range of the Fluke 17XX Energy or Power Logger to 6000A AC while providing the ultimate measurement flexibility. The iFlex probes connect directly to the energy logger, displaying current measurements without error prone scaling factors. The 1.8 m (6 ft) cord allows separation between the measurement location and the energy logger making it easier to view the display. Fluke 17XX iFlex cables are available in 12, 24, and 36 inch.



Ordering information



I17XX-FLEX6000

6000A 36 inch iFlex® Current Clamps



Fluke. Keeping your world up and running.®

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

BUT. FLUKE SOUTH EAST ASIA PTE LTD

Menera Satu Sentra Kelapa Gading #06-05 JI. Bulevar Kelapa Gading Kav. LA# No. 1

Summarecon Kelapa Gading

Jakarta Utara 14240 Indonesia

Tel: +62 21 2938 5922 Email: info.asean@fluke.com www.fluke.com/id-en

©2025 Fluke Corporation. Specifications subject to

change without notice.

04/2025

In the U.S.A. (800) 443-5853 In Europe/M-East/Africa +31 (0)40 267 5100 In Canada (800)-36-FLUKE

For more information call:

From other countries +1 (425) 446-5500

Modification of this document is not permitted without written permission from Fluke

Corporation.