

**TECHNICAL DATA** 

# Liquid Trap



## **Key features**

- Working pressure range: 3000 psi (206 bar).
- Includes convenient drain valve and mounting stand.
- Place between device under test and calibrator.
- 1/4 inch NPT fittings.

## Product overview: Liquid Trap

The 7000-102 Liquid Trap can be used with most any pneumatic test or calibration system where liquid contamination may be present in the device under test. Although the preferred procedure is to insure the device under test is free of both liquid and particulate contamination prior to calibration, the 7000-102 provides a degree of insurance to protect the calibration instrument.

The 7000-102 can be used with any calibrator, including the Model 7010 and complete line of Series 7215 Digital Pressure Controllers. It can assist with minimizing the possibility of contamination of the unique Ruska quartz sensor found in these instruments along with the control valves and solenoid valves, all of which are designed for pneumatic operation and can be damaged when exposed to liquids.

The 7000-102 is also compatible with Druck's line of pressure controllers including the DPI 515 and DPI 520 Digital Pressure Calibrators.

Further, the 7000-102 can be used with virtually any test or calibration system where the pressure does not exceed 3000 psi.

A convenient drain valve allows periodic removal of accumulated liquids. Due to the pressure range, the level inside the Trap cannot be observed. Therefore it is recommended that the drain valve be opened on a frequent basis or prior to each test. A fitting is provided on the drain valve to allow connection to tubing that can run to a container for disposal.



The 7000-102 Liquid Trap is provided with a bench mount stand with two mounting holes for a sturdy installation.

## Specifications: Liquid Trap

| Specifications            |                           |
|---------------------------|---------------------------|
| Maximum Pressure          | 3000 psig (206 bar)       |
| Fiing type                | ¼ in NPT, stainless steel |
| Materials of construction | 300 stainless steel       |
| Inteal Volume             | 9 cu.in. (150 cc)         |



## Ordering information



### Liquid Trap

### 7000-102

Liquid trap assembly



### Fluke. Keeping your world up and running.®

Fluke Corporation PO Box 9090, Everett, WA 98206 U.S.A.

#### BUT. FLUKE SOUTH EAST ASIA PTE LTD

Menera Satu Sentra Kelapa Gading #06-05 JI. Bulevar Kelapa Gading Kav. LA# No. 1 Summarecon Kelapa Gading Jakarta Utara 14240 Indonesia Tel: +62 21 2938 5922 Email: info.asean@fluke.com www.fluke.com/id-en ©2025 Fluke Corporation. Specifications subject to change without notice. 04/2025

Modification of this document is not permitted without written permission from Fluke Corporation.

### For more information call:

In the U.S.A. (800) 443-5853 In Europe/M-East/Africa +31 (0)40 267 5100 In Canada (800)-36-FLUKE From other countries +1 (425) 446-5500