

TECHNICAL DATA

Fluke TPS VOLTPROBE 100 V**Specifications: Fluke TPS VOLTPROBE 100 V**

Specifications	
Range rms	1 V to 170 V
Vnom	100 V
Vmax. contin.	1000 V
Fast transient range Vp < 1 ms	6000
Iinsic error	0.15%
Operating voltage	600 V CAT IV

Ordering information



Fluke TPS

Fluke. *Keeping your world up and running.®*

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:

In the U.S.A. (800) 443-5853

In Europe/M-East/Africa

+31 (0)40 267 5100

In Canada (800)-36-FLUKE

From other countries +1 (425) 446-5500

BUT. FLUKE SOUTH EAST ASIA PTE LTD

Menera Satu Sentra Kelapa Gading #06-05

Jl. Bulevar Kelapa Gading Kav. LA# No. 1

Summarecon Kelapa Gading

Jakarta Utara 14240

Indonesia

Tel: +62 21 2938 5922

Email: info.asean@fluke.com

www.fluke.com/id-en

©2025 Fluke Corporation. Specifications subject to change without notice.

03/2025

Modification of this document is not permitted without written permission from Fluke Corporation.