

TECHNICAL DATA

# P5544 Two Gauge Stand



## Product overview: P5544 Two Gauge Stand

This adapter mounts directly to the test port of the calibrator and allows for the calibration of two instruments at the same time or the connection of a reference test instrument. Maximum working pressure is 10,000 psi (700 bar).

## Specifications: P5544 Two Gauge Stand

Specifications	
Body Material	Brass and Stainless steel
O-Rings	Nitrile
Test Port Adapters	1 set, 1/8, 1/4, 3/8 and 1/2 NPT or BSP and adapters supplied with calibrator
Calibrator Test Connection	1/2 BSP male (mating adapter supplied)

## Ordering information



### **P5544**

P5544 Two Gauge Stand

---

**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**

PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**

In the U.S.A. (800) 443-5853

In Europe/M-East/Africa

+31 (0)40 267 5100

In Canada (800)-36-FLUKE

From other countries +1 (425) 446-5500

**BUT. FLUKE SOUTH EAST ASIA PTE LTD**

Menera Satu Sentra Kelapa Gading #06-05

Jl. Bulevar Kelapa Gading Kav. LA# No. 1

Summarecon Kelapa Gading

Jakarta Utara 14240

Indonesia

Tel: +62 21 2938 5922

Email: info.asean@fluke.com

[www.fluke.com/id-en](http://www.fluke.com/id-en)

©2025 Fluke Corporation. Specifications subject to change without notice.

04/2025

**Modification of this document is not permitted without written permission from Fluke Corporation.**