

TECHNICAL DATA

Fluke Calibration 9009 Dual-Well Dry-Well



Key features

- Temperature ranges from $-15\text{ }^{\circ}\text{C}$ to $350\text{ }^{\circ}\text{C}$.
- Two wells in each block for simultaneous comparison calibrations.
- The cold block is calibrated to within $\pm 0.2\text{ }^{\circ}\text{C}$ with stability of $\pm 0.05\text{ }^{\circ}\text{C}$. The hot block's display is accurate to $\pm 0.6\text{ }^{\circ}\text{C}$ with stability of $\pm 0.05\text{ }^{\circ}\text{C}$.
- Rugged, lightweight, and water-resistant enclosure.

Product overview: Fluke Calibration 9009 Dual-Well Dry-Well

The Model 9009 includes two independently controlled temperature blocks. The hot block provides temperatures from $50\text{ }^{\circ}\text{C}$ to $350\text{ }^{\circ}\text{C}$, while the cold block covers the range $-15\text{ }^{\circ}\text{C}$ to $110\text{ }^{\circ}\text{C}$. Each block is controlled by a precision Hart Scientific temperature controller. These aren't some off-the-shelf controllers we glued into a box. These are Hart Scientific controllers from the leading temperature company in the world.

Each temperature block includes two wells with removable inserts. You can calibrate four probes at once, or you can calibrate two probes at the same time with an external reference (like Hart's Model 1521 LLK Thermometer), or you can use the two temperature wells to get quick "zero" and "span" references for transmitter calibrations.

Need portability and durability? The 9009 is housed in a tough Pelican™ case that is both airtight and watertight. It's a small package weighing only 10 pounds, yet it fits everything you need, including a power cord and four extra inserts. Inserts are available to accommodate sensors of any size from $1/16\text{''}$ (1.6 mm) to $7/16\text{''}$ (11.1 mm). This rugged system

can go anywhere.

Of course the 9009 also delivers the performance you expect from a Hart Scientific temperature source. The cold block is calibrated to within ± 0.2 °C with stability of ± 0.05 °C. The hot block's display is accurate to ± 0.6 °C with stability of ± 0.05 °C. A NIST-traceable calibration is included for each of the two test blocks.

For use with automated systems, the 9009 comes with an RS-232 connection, which allows you to control and monitor temperatures from your PC. For completely automated calibrations, Hart's MET/TEMP II software also integrates with the 9009.

Two blocks in one unit, a total range of -15 °C to 350 °C, portability, durability, versatility, performance, automation. Hart Scientific delivers it all.

Specifications: Fluke Calibration 9009 Dual-Well Dry-Well

General Specifications		
	Hot block	Cold block
Range	50°C to 350°C (122°F to 662°F)	-15°C to 110°C (5°F to 230°F) (-8°C [18°F] with hot block at 350°C [662°F])
Accuracy	± 0.6 °C	± 0.2 °C
Stability	± 0.05 °C	
Well-to-well uniformity	± 0.1 °C	
Display resolution	0.1°	
Heating times	30 minutes from 25°C to 350°C	15 minutes from 25°C to 110°C
Cooling times	40 minutes from 350°C to 100°C	16 minutes from 25°C to -15°C
Stabilization times	8 minutes	
Well depth	4 in (102 mm)	
Removable inserts	Two 6.4 mm (1/4 in) and two 4.8 mm (3/16 in) inserts included; see ordering information for other available inserts	
Computer interface	RS-232 included	
Power	115 V AC (± 10 %), 3 A, or 230 V AC (± 10 %), 2 A, specify, 50/60 Hz, 280 W	
Size (H x W x D)	178 x 267 x 248 mm (7 x 10.5 x 9.75 in)	
Weight	4.5 kg (10 lb)	
NIST-traceable calibration	Data at 50°C, 100°C, 150°C, 200°C, 250°C, 300°C, and 350°C	Data at -8°C, 0°C, 25°C, 50°C, 75°C, 100°C, and 110°C

Ordering information



Fluke 9009-B-156

Fluke Calibration 9009 Dual-Well Dry-Well, Dual Block (Black), 110V 50/60HZ

Includes two 1/4 in (6.4 mm) and two 3/16 in (4.8 mm) inserts.

Fluke 9009-Y-156

Fluke Calibration 9009 Dual-Well Dry-Well, Dual Block (Yellow), 110V 50/60HZ

Includes two 1/4 in (6.4 mm) and two 3/16 in (4.8 mm) inserts.

Fluke. *Keeping your world up and running.®*

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:

In the U.S.A. (800) 443-5853

In Europe/M-East/Africa

+31 (0)40 267 5100

In Canada (800)-36-FLUKE

From other countries +1 (425) 446-5500

BUT. FLUKE SOUTH EAST ASIA PTE LTD

Menera Satu Sentra Kelapa Gading #06-05

Jl. Bulevar Kelapa Gading Kav. LA# No. 1

Summarecon Kelapa Gading

Jakarta Utara 14240

Indonesia

Tel: +62 21 2938 5922

Email: info.asean@fluke.com

www.fluke.com/id-en

©2025 Fluke Corporation. Specifications subject to change without notice.

04/2025

Modification of this document is not permitted without written permission from Fluke Corporation.