

TECHNICAL DATA

# Fluke Networks MS2-TTK MicroScanner<sup>2</sup> Network Cable Tester Kit



## Key features

- Graphical wire map, length, cable ID, & distance to fault
- MicroScanner<sup>2</sup> cable tester, punch down tool, tone generator & probe
- Tests all common media types including RJ11, RJ45, & Coax
- Locates virtually any cable w/ IntelliTone™ digital & analog toning
- Verifies media services: 10/100/1000 Ethernet, POTS, & PoE

## Product overview: Fluke Networks MS2-TTK MicroScanner<sup>2</sup> Network Cable Tester Kit

MS2-TTK MicroScanner<sup>2</sup> copper cable verifier kit helps find common errors by displaying graphical wiremap, pair lengths, distance to fault, and far end device. Integrated RJ11, RJ45, and coax test ports support many types of low-voltage cable testing with no need for adapters.

## Specifications: Fluke Networks MS2-TTK MicroScanner<sup>2</sup> Network

# Cable Tester Kit

MicroScanner<sup>2</sup> and MicroScanner PoE Specifications

Specifications apply at 23 °C (73 °F), unless otherwise noted.

Environmental Specifications	
Operating temperature	32 °F to 113 °F (0 °C to 45 °C)
Storage temperature	-4 °F to +140 °F (-20 °C to +60 °C)
Operating relative humidity (% RH without condensation)	90 % (50 °F to 95 °F 10 °C to 35 °C) 75 % (95 °F to 113 °F 35 °C to 45 °C)
Shock and Vibration	Random, 2 g, 5 Hz-500 Hz (Class 2) 1 m drop test with and without wiremap adapter aached
Safety	IEC 61010-1 3rd Edition
Altitude	4,000 m; Storage: 12,000 m
EMC	IEC 61326-1
General Specifications	
Test connectors	Shielded 8-pin modular jack accepts 8-pin modular (RJ45) and 4-pin modular (RJ11) plugs. MicroScanner <sup>2</sup> : F-connector for coaxial cable.
Power	Baery type: 2 AA (NEDA 15A, IEC LR6) alkaline baeries Baery life: 20 hours of typical use Other compatible baery types: 2 AA photo lithium, NIMH, NICAD
Dimensions and weight (with baeries installed and wiremap adapter aached)	3 in x 6.4in x 1.4 in (7.6 cm x 16.3 cm x 3.6 cm) MicroScanner <sup>2</sup> : 10.6 oz (300 g) MicroScanner PoE: 10.6 oz (300 g)
Display	Monochrome LCD with backlight
Test Modes	
Cable test	Measures length, verifies wiremap, identifies remote ID locators, and detects Etheet ports. MicroScanner PoE also shows HIGH $\Omega$ when the resistance of the cable is more than 12.5 $\Omega$ . Displays results on one screen.
Tone	Generates Intellitone™ and normal analog toning signals
PoE	MicroScanner <sup>2</sup> : Solicits and detects the presence of 802.3af compatible PoE (Power over Etheet) devices MicroScanner PoE: Solicits and detects the presence of 802.3af, at, bt, and UPOE (Cisco's Universal Power over Etheet) compatible PoE devices
Performance Specifications	
Cable types tested	Twisted pair: UTP, FTP, SSTP Coaxial (MicroScanner <sup>2</sup> ): 75 $\Omega$ , 50 $\Omega$ , 93 $\Omega$
Length test	Range: 460 m (1500 ft) Resolution: 0.3 m (1 ft) Typical accuracy: $\pm$ 4% or 0.6 m (2 ft) whichever is greater. NVP uncertainty is an additional error. Calibration: User-seable NVP for twisted pair and coax (MicroScanner <sup>2</sup> ). Can determine actual NVP with known length of cable.

Wiremap test	Detects single-wire faults, shorts, miswires, split pairs, and up to seven far-end adapter IDs. The wiremap is drawn with proportional length to visually indicate the approximate location of faults.
Etheet port detection	MicroScanner <sup>2</sup> : Detects the advertised speed of 802.3 Etheet ports with speeds of 10 Mbps, 100 Mbps, and 1 Gbps. MicroScanner PoE: Detects the advertised speed of 802.3 Etheet ports with speeds of 10 Mbps, 100 Mbps, 1 Gbps, 2.5 Gbps, 5 Gbps, and 10 Gbps.
Tone generator	Supports toning and cable mapping with a Fluke Networks digital IntelliTone™ probe. Generates four tones compatible with typical analog probes. SmartTone™ feature gives positive identification of cables in bundles when using an IntelliTone or an analog probe.

**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**

PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**

In the U.S.A. (800) 443-5853

In Europe/M-East/Africa

+31 (0)40 267 5100

In Canada (800)-36-FLUKE

From other countries +1 (425) 446-5500

**BUT. FLUKE SOUTH EAST ASIA PTE LTD**

Menera Satu Sentra Kelapa Gading #06-05

Jl. Bulevar Kelapa Gading Kav. LA# No. 1

Summarecon Kelapa Gading

Jakarta Utara 14240

Indonesia

Tel: +62 21 2938 5922

Email: info.asean@fluke.com

www.fluke.com/id-en

©2025 Fluke Corporation. Specifications subject to change without notice.

04/2025

**Modification of this document is not permitted without written permission from Fluke Corporation.**