

TECHNICAL DATA

55XXA/DMMCAL | DMM Autocal Adapter











Product overview: 55XXA/DMMCAL | DMM Autocal Adapter

The 55XXA/DMMCAL AUTOCAL ADAPTER is a lead set that connects to the 5560A, 5550A or 5540A Multi-Product Calibrators' output blocks at one end and to a device under test (DUT) on the other. The adapter minimizes manual lead connections during the verification process.

Specifications: 55XXA/DMMCAL | DMM Autocal Adapter

DMM Input/Sense coax cables: 1020 Vrms max

LO I Current: 3.2 A max

3 Fluke Corporation 55XXA/DMMCAL | DMM Autocal Adapter



HI I Current: 15 A max



Ordering information



55XXA/DMMCAL

DMM Autocal Adapter



$\textbf{Fluke}. \ \textit{Keeping your world up and running.} \\ \textbf{@}$

Fluke (UK) Ltd.
52 Hurricane Way
Norwich, Norfolk
NR6 6JB
United Kingdom
Tel.: +44 (0)20 7942 0708
E-mail: cs.uk@fluke.com
www.fluke.com

©2025 Fluke Corporation. All rights reserved. Data subject to alteration without notice. 04/2025

Modification of this document is not permitted without written permission from Fluke Corporation.