

TECHNICAL DATA

55XXA/COIL 50 | 50-Turn Current Coil



Product overview: 55XXA/COIL 50 | 50-Turn Current Coil

Optional 50-turn current coil expands workload coverage for calibrating clamp meters and ammeters.

Includes an Accredited 17025 Calibration Certificate Traceable to International Standards with Data.

Specifications: 55XXA/COIL 50 | 50-Turn Current Coil

Specifications	
Number of turns	50
Maximum current	20 A rms, continuous 30.2 A rms, 5 minutes



Maximum voltage, all inputs	30 V to Earth
Minimum inner diameter of clamp jaws	23 mm
Coil ratio	$\pm 0.65\%$ , 3 Hz to 440 Hz. Usable but unspecified at dc and above 440 Hz

## Ordering information



### **55XXA/COIL 50**

50-Turn Current Coil

---

Includes an Accredited 17025 Calibration Certificate Traceable to International Standards with Data

---

**Fluke.** *Keeping your world up and running.®*

**Fluke (UK) Ltd.**  
52 Hurricane Way  
Norwich, Norfolk  
NR6 6JB  
United Kingdom  
Tel.: +44 (0)20 7942 0708  
E-mail: [cs.uk@fluke.com](mailto:cs.uk@fluke.com)  
[www.fluke.com](http://www.fluke.com)

©2025 Fluke Corporation. All rights reserved.  
Data subject to alteration without notice.  
05/2025

**Modification of this document is not permitted  
without written permission from Fluke  
Corporation.**