

TECHNICAL DATA

VPS210-R Voltage Probe Set, 200 MHz, Red (one, red)



Product overview: VPS210-R Voltage Probe Set, 200 MHz, Red (one, red)

Double insulated voltage probe for ScopeMeter 190 series.

Each probe set includes:

- 600 V CAT III / 1000 V CAT II rated 10:1 Voltage Probe
- Hook Clip for Probe Tip
- Ground Lead with Mini Alligator
- Insulation Sleeve
- 30 V CAT II rated Ground Spring for Probe Tip

Specification:

- Attenuation: 10x
- Bandwidth: 200 MHz



- Max. Input Voltage: 1000 V CAT II or 600 V CAT III
- Max. Voltage to ground: 1000 V CAT II or 600 V CAT III per IEC / EN61010-031
- Input Resistance: 10 M?
- Input Capacitance: 12 pF
- Compensation range: 10 to 22 pF
- Cable Length: 1.2 m

Specifications: VPS210-R Voltage Probe Set, 200 MHz, Red (one, red)

| Specification | |
|------------------------|--|
| Aenuation | 10x |
| Bandwidth | 200 MHz |
| Max. input voltage | 1000 V CAT II or 600 V CAT III |
| Max. voltage to ground | 1000 V CAT II or 600 V CAT III per IEC / EN61010-031 |
| Input resistance | 10 ΜΩ |
| Input capacitance | 12 pF |
| Compensation range | 10 to 22 pF |
| Cable length | 1.2 m |



Fluke. Keeping your world up and running.®

Fluke (UK) Ltd. 52 Hurricane Way Norwich, Norfolk NR6 6JB United Kingdom Tel.: +44 (0)20 7942 0708 E-mail: cs.uk@fluke.com ©2025 Fluke Corporation. All rights reserved. Data subject to alteration without notice. 03/2025

Modification of this document is not permitted without written permission from Fluke Corporation.