

TECHNICAL DATA

Standard 30 mm Infrared Lens



Product overview: Standard 30 mm Infrared Lens

Standard field of view lens for use in most applications – compatible with TiX1000, TiX660 and TiX640 models.

Applications: Research and development, utilities, predictive maintenance, industrial quality control, building inspection, aerial imagery, and veterinary.

Specifications: Standard 30 mm Infrared Lens

| General Characteristics | |
|-------------------------|---------------|
| Lens description | Standard lens |
| Focal distance | 30 mm |
| Focus | 0.72 mm |
| 1024 x 768 | |
| iFOV | 0.6 mRad |
| FOV | 32.4 x 24.7° |
| 640 x 480 | |

| | |
|------|--------------|
| iFOV | 0.8 mRad |
| FOV | 30.9 x 23.1° |

Ordering information



FLK-XLENS/STAN

Applications: Research and development, utilities, predictive maintenance, industrial quality control, building inspection, aerial imagery, and veterinary.

Compatible with TiX1000, TiX660 and TiX640 infrared cameras.

Fluke. *Keeping your world up and running.®*

Fluke (UK) Ltd.
52 Hurricane Way
Norwich, Norfolk
NR6 6JB
United Kingdom
Tel.: +44 (0)20 7942 0708
E-mail: cs.uk@fluke.com
www.fluke.com

©2025 Fluke Corporation. All rights reserved.
Data subject to alteration without notice.
04/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**