

TECHNICAL DATA

# PLS 6R Laser Levels







## Key features

- Accuracy:  $\pm 1/8$  in at 30 ft. ( $\pm 3$  mm @ 10 m)
- Red beam laser
- Point Laser Direction: 90° up, down, left, right
- Horizontal fan angle: 180 °
- Vertical fan angle: 130°
- Durable pendulum lock
- IP54 rating to limit dust and water entry for years of operation on the job site.

## Product overview: PLS 6R Laser Levels

The new PLS 6R red laser levels offer the durability and precision you expect from PLS, a Fluke Company. We've replaced the PLS 4 red with the PLS 6 and created both a red and green version. The fast settling, self-leveling pendulum gives you accurate point and reference lines almost instantly. Additionally, these products feature a pendulum lock to secure the laser during transport or if dropped.

- Plumb, level, and square with one tool. This professional self-leveling combination point and cross line laser level in red and green includes vertical and horizontal modes with lines and points combined. Great for metal or wood stud installation, general layout, square alignment, or finish carpentry.
- Kit includes floor stand, magnetic L-bracket, and UB9 wall and ceiling bracket for fast, easy overhang and centerline measurements.
- System includes the SLD laser line detector for use in bright lighting, long distances, or outdoors.

## Specifications: PLS 6R Laser Levels

Rotary levels	PLS 6R, 6G
<b>Baery</b>	3 x AA Alkaline IEC LR6
<b>Baery Life, Continuous Use</b>	
<b>Red</b>	□ 8 hours (both lasers)
<b>Green</b>	□ 3 hours (both lasers)
<b>Point Laser Direction</b>	90° up, down, left, right
<b>Line Fan Angle</b>	
<b>Horizontal</b>	□ 180°
<b>Vertical</b>	□ 130°
<b>Working Range</b>	
<b>Point Laser (6 only)</b>	□30 m (100 ft.)
<b>Line Laser</b>	
<b>Without SLD</b>	□15 m (50 ft.)
<b>With SLD</b>	6 m to 60 m (20 ft. to 200 ft.)
<b>Accuracy</b>	□3 mm @ 10 m (□1/8 in at 30 ft.)
<b>Laser Leveling</b>	
<b>System</b>	Automatic, Pendulum
<b>Range</b>	4°
<b>Line Laser Width</b>	□2 mm at 5 m
<b>Temperature</b>	
<b>Operating</b>	-10 °C to 50 °C (14 °F to 122 °F)
<b>Storage</b>	
<b>With Baeries</b>	-18 °C to 50 °C (-0.4 °F to 122 °F)
<b>Without Baeries</b>	-20 °C to 70 °C (-13 °F to 158 °F)
<b>Relative Humidity</b>	0 % to 90 % (0 °C to 35 °C) 0 % to 75 % (35 °C to 40 °C) 0 % to 45 % (40 °C to 50 °C)
<b>Size (H x W x L)</b>	116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in)
<b>Weight</b>	~ 0.6 kg (1.3 lb.)
<b>Safety</b>	IEC 61010-1: Pollution Degree 2
<b>Laser</b>	IEC 60825-1:2014 Class 2
<b>Light Source</b>	Semiconductor laser diode
<b>Max Output Power</b>	< 1 mW
<b>Wavelength</b>	
<b>Red</b>	635 nm ± 5 nm



<b>Green</b>	525 nm ± 5 nm
<b>Electromagnetic compatibility (EMC)</b>	
<b>Inteational</b>	<p>IEC 61326-1: Basic Electromagnetic Environment CISPR 11: Group 1, Class B</p> <p>Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the inteal function of the equipment itself.</p> <p>Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes.</p> <p>Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object</p>
<b>Korea (KCC)</b>	Class B Equipment (Broadcast communications equipment for home)
<b>USA (FCC)</b>	47 CFR 15 subpart B. This product is considered an exempt device per clause 15.103.



**Fluke.** *Keeping your world up and running.®*

**Fluke (UK) Ltd.**  
52 Hurricane Way  
Norwich, Norfolk  
NR6 6JB  
United Kingdom  
Tel.: +44 (0)20 7942 0708  
E-mail: cs.uk@fluke.com  
www.fluke.com

©2025 Fluke Corporation. All rights reserved.  
Data subject to alteration without notice.  
03/2025

**Modification of this document is not permitted  
without written permission from Fluke  
Corporation.**