

TECHNICAL DATA

7008/7037/7012/7011 Refrigerated Temperature Calibration Baths





Key features

- High temperature stability to ± 0.0007 °C.
- Set-point resolution to 0.00003 °C.
- Exceptional temperature stability (± 0.0015 °C) and uniformity (± 0.003 °C) at low temperatures down to -40 °C.

Product overview: 7008/7037/7012/7011 Refrigerated Temperature Calibration Baths

These four baths operate at temperatures as low as -40 °C, and each one is built using CFC-free refrigerants. Fluke Calibration's proprietary controller design and unique tank construction produce bath stabilities to ± 0.001 °C or better. These baths are so stable and uniform that national labs use them for comparison calibrations and fixed-point cell maintenance.

Each bath (except the 7011) is fully automatable with a bath interface package and Fluke Calibration's MET/TEMP II automation software package. When we automate a bath, we automate it completely with computer-controlled solenoid valves for precision balancing of the heating and cooling system. MET/TEMP II performs all calibration tasks automatically, using your PC.

With a Fluke Calibration cold bath, you can forget external coolants. Internal refrigeration systems are all that's needed to reach each bath's coldest temperature. Most cold baths may be ordered with an optional pumping lid for supplying external cooling requirements.

Each bath has unique characteristics that make it perfect for specific jobs. Some baths are excellent for SPRTs, some are great with thermistors, and some are perfect for maintaining triple point of water cells. A 7008IR bath can even be used to maintain the temperature of a blackbody cone.

Regardless of your application, Fluke Calibration has a bath that gets the job done, and done better than anyone else can do it. Call us today and tell us about your application.

Specifications: 7008/7037/7012/7011 Refrigerated Temperature Calibration Baths

Specifications				
Model	7008	7037	7012	7011
Range	-5 °C to 110 °C	-40 °C to 110 °C	-10 °C to 110 °C	
Stability	± 0.0007 °C at 25 °C (water) ± 0.001 °C at 25 °C (mineral oil)	± 0.002 °C at -40 °C (ethanol) ± 0.0015 °C at 25 °C (water) ± 0.003 °C at 100 °C (oil 5012)	± 0.0008 °C at 0 °C (ethanol) ± 0.0008 °C at 25 °C (water) ± 0.003 °C at 100 °C (oil 5012)	
Uniformity	± 0.003 °C at 25 °C (water) ± 0.004 °C at 25 °C (mineral oil)	± 0.004 °C at -40 °C (ethanol) ± 0.002 °C at 25 °C (water) ± 0.004 °C at 100 °C (oil 5012)	± 0.003 °C at 0 °C (ethanol) ± 0.002 °C at 25 °C (water) ± 0.004 °C at 100 °C (oil 5012)	

Temperature Seing	Digital display with push-buon data ey		
Set-Point Resolution	0.002 °C; high-resolution mode, 0.00003 °C	0.01 °C; high-resolution mode, 0.00007 °C	0.002 °C; high-resolution mode, 0.00003 °C
Display Resolution	0.01 °C		
Digital Seing Accuracy	±1 °C		
Digital Seing Repeatability	±0.01 °C		±0.005 °C
Heaters	500 and 1000 Was		
Access Opening (call for customs)	324 x 184 mm(12.75 x 7.25 in)	162 x 292 mm(6.38 x 11.5 in)	127 x 254 mm(5 x 10 in)
Depth	331 mm (13 in)	457 mm (18 in)	305 mm (12 in)
Weed Parts	304 Stainless Steel		
Power	115 VAC (±10 %), 60 Hz, 14 A or 230 VAC, 50 or 60 Hz, 8 A, specify	115 VAC (±10 %), 60 Hz, 16 A or 230 VAC (±10 %), 50 or 60 Hz, 9 A (specify voltage and frequency)	115 VAC (±10 %), 60 Hz, 14 A or 230 VAC (±10 %), 50 Hz, 7 A, specify
Volume	42 liters (11.2 gal)	42 liters (11.2 gal)	27 liters (7.2 gal)
Weight	61 kg (135 lb)	68 kg (150 lb)	56.7 kg (125 lb)
Size	610 x 775 x 483 mm (24 x 30.5 x 19 in)	775 x 768 x 483 mm (30.5 x 30.25 x 19 in)	762 x 686 x 401 mm (30 x 27 x 15.8 in) 559 x 686 x 401 mm (22 x 27 x 15.8 in)
Automation	Use the 1586A Super-DAQ to automate temperature sensor calibration		

Ordering information

**7008**

Standard Bath, -5 °C to 110 °C, high capacity

7011

Standard Bath, -10 °C to 110 °C

7012

Standard Bath, -10 °C to 110 °C, deep

7037

Standard Bath, -40 °C to 110 °C, deep

7008IR

7008 Bath, modified to accept an IR cone

2033

IR Cone (NIST design)

2016-7008

Fluid Level Adapter, 7008

2016-7011

Fluid Level Adapter, 7011

2016-7012

Fluid Level Adapter, 7012

2016-7037

Fluid Level Adapter, 7037

2016-7040

Fluid Level Adapter, 7040

2071

Bath Cart, 7011, 7012 (312 mm [12.3 in] H)

Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2025 Fluke Corporation.
Specifications subject to change without notice.
04/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**