

TECHNICAL DATA

# Fluke 80PK-11 Type-K Flexible Cuff Thermocouple Temperature Probe



## Key features

- Designed for hands free measurement of HVAC temperature measuring applications
- Use multiple and leave in place for route based routine maintenance
- Use with any temperature-measuring instrument designed to accept Type-K thermocouples

## Specifications: Fluke 80PK-11 Type-K Flexible Cuff Thermocouple Temperature Probe

Specifications	
Measurement range	-30°C to 150°C (-19.3°F to 302°F)
Accuracy	±1.5°C (±2.7°F)
Measurement time (time constant)	10 seconds
Maximum voltage	24 V AC rms or 60 V DC maximum for proper safe operation.
Maximum temperature	150°C (302°F)

Cable	<b>Total length</b>	1 m (40 in), 0.97 m (38 in) lead wire, 49.5 cm (19.5 in) fabric hook-and-loop fastener cuff
	Insulation material	Hytrel
	Width of attachment material	2.5 cm (1 in)
	Min usable pipe diameter	3.8 cm (1.5 in)
	Max. usable pipe diameter	14 cm (5.5 in)
Connector	<b>Type</b>	Yellow mini-thermocouple with 0.500 in pin
	Material	Hytrel 4774
	Maximum temperature	200°C (392°F)

## Ordering information



**Fluke 80PK 11**

---

**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Canada (800) 36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com](http://www.fluke.com)

©2025 Fluke Corporation.  
Specifications subject to change without notice.  
04/2025

**Modification of this document is not permitted  
without written permission from Fluke  
Corporation.**