

TECHNICAL DATA

Fluke TL1500DC Insulated Test Leads









Key features

- Measures voltage safely and accurately up to 1500 V DC
- CAT III 1500 V CAT IV 600 V with protective cap / CAT II 1500 V without protective cap, 10A
- Compatible with most Fluke clamp meters and multimeters
- Comes with one-year warranty
- 39.3 inches (1 meter) long

Product overview: Fluke TL1500DC Insulated Test Leads

The Fluke TL1500DC test leads provide safe and accurate voltage measurements up to 1500 V DC, commonly found in solar, wind, and battery applications. These insulated test leads made of PVC material are safety rated CAT III 1500 V, CAT IV 600 V with the protective cap and CAT II 1500 V without protective cap for use in different environments.

Specifications: Fluke TL1500DC Insulated Test Leads


Ratings:	IEC 61010-031 CAT II 1500 V, CAT III 1500 V, CAT IV 600 V, 10 A
Compatibility:	Compatible with all instruments that accept standard 4 mm shrouded banana plugs
Pollution:	Pollution Degree 2, 2000 m altitude
Environmental ratings:	Operating -10C to 50C



Storage:	-20 °C to 60 °C @ < 80 % RH
oto. age.	20 2 10 00 2 6 00 70 10 1



Ordering information



Fluke TL1500DC

Fluke TL1500DC Insulated Test Leads

Includes:

- One pair (red, black) TL1500DC Insulated Test Leads
- Two protective caps
- One-year warranty



Fluke. Keeping your world up and running.®

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call: In the U.S.A. (800) 443-5853

In Canada (800) 36-FLUKE From other countries +1 (425) 446-5500 www.fluke.com ©2025 Fluke Corporation.

Specifications subject to change without notice.

04/2025

Modification of this document is not permitted without written permission from Fluke Corporation.