

TECHNICAL DATA

Fluke 707Ex Intrinsically Safe mA Loop Calibrator



Key features

- High performance intrinsically safe loop calibrator for use in potentially explosive environments
- Is certified in accordance with ATEX directive (Ex II 2 G Ex ia IIC T4) in Zones 1 and 2 and to operate in accordance with Factory Mutual N.I. Class 1, Division 2 areas Group A-D
- Features large display and simple, quick-click interface for easy one-handed operation

Product overview: Fluke 707Ex Intrinsically Safe mA Loop Calibrator

Fluke 707Ex for fast one-handed mA loop checks in Ex zones

The Fluke 707Ex is an intrinsically safe loop calibrator for use in potential explosive environments. The Fluke 707Ex is certified in accordance with the ATEX directive in Zones 1 and 2. The Fluke 707Ex is certified in accordance with the ATEX directive (Ex II 2 G Ex ia IIC T4) in Zones 1 and 2. It is also certified to operate in accordance with Factory Mutual N.I. Class 1, Division 2 areas Group A-D.

Beyond that it combines the best features of a push-button and knob-base loop calibrator, for extremely fast and easy calibration. The large display and simple quick-click rotary button lets you make quick selections and adjustments with one hand. Plus, features such as mA sourcing, simulation and measurement; simultaneous display of mA and % of

span, and selectable step or ramp outputs, helps you work more efficiently and accurately. And you can quickly change the 9V battery without breaking the calibration seal.

Other useful features:

- Provides simultaneous mA and % readout for quick, easy interpretation of readings.
- Delivers superior mA accuracy of 0.015%
- Provides 1 μ A resolution for mA source, simulate, and measure
- Includes HART® compatible resistance connected in series with the loop supply for compatibility with HART communicators
- Features push button 25% steps for fast, easy linearity checks
- Includes 0-100% "span check" for fast confirmation of zero and span.
- Provides selectable slow ramp, fast ramp, and step ramp to provide smooth outputs for valve slewing and loop functional tests.
- Includes a 24 volt internal loop supply, so you can power and read a transmitter at the same time without a DMM.
- Measures V DC to 28 V
- Runs on a single 9 V battery that is easily changed without breaking the calibration seal
- Offers 0 - 20 mA or 4 - 20 mA default start up modes
- Features an innovative output adjustment dial
- Comes with a protective yellow holster with test lead storage and a three year warranty

Specifications: Fluke 707Ex Intrinsically Safe mA Loop Calibrator

Specifications		
Current measurement	Range	0 to 24 mA
	Resolution	0.001 mA
	Accuracy	0.015% Rdg + 2 LSD
Current sourcing	Range	0 to 20 mA or 4 to 20 mA
	Accuracy	0.015% Rdg + 2 LSD
	Drive capability	700 Ω at 20 mA
Current simulation	Range	0 to 20 mA or 4 to 20 mA
	Accuracy	0.015% Rdg + 2 LSD
Loop power	While measuring mA, 24 V	
Voltage measurement	Range	0 to 28 V DC
	Resolution	1 mV
	Accuracy	0.015% Rdg + 2 LSD
Environmental Specifications		
Operating temperature	-10°C to 55°C	
Storage temperature	-40°C to 60°C	
Humidity (without condensation)	0 to 95% (0°C to 30°C);	
	0 to 75% (30°C to 40°C)	
	0 to 45% (40°C to 50°C)	

Temperature coefficient	-10°C to 18°C, 28°C to 55°C, $\pm 0.005\%$ of range per °C
Safety Specifications	
Safety	CSA C22.2 No. 1010.1:1992
EMC	EN50082-1:1992 and EN55022:1994 Class B
Maximum voltage	30 V
ATEX certification	Ex II G Ex ia IIC T4 Zones 1 and 2, ZELM 02 ATEX 0120 X
CE certification	EN61010-1 and EN61326
Mechanical and General Specifications	
Size	152 x 70 x 41 mm
Weight	224 g (350 g including holster)
Baeries	One 9V baery Alkaline
Warranty	3 year
Shock & vibration	per MIL-T-28800 for a Class 2 Instrument
Display current and % of span	Yes
Auto step, auto ramp	Yes
Span check	Yes

Ordering information



Fluke 707Ex

Fluke 707Ex Intrinsically Safe Loop Calibrator

Includes:

- Alligator test clips
- Instruction manual (on CD-ROM)
- Protective holster with Flex-Stand™
- Safety designed test leads
- NIST- traceable calibration report and data



Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2025 Fluke Corporation.
Specifications subject to change without notice.
04/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**