

TECHNICAL DATA

HART DRYWELL CABLE | An interface cable kit that includes a null modem to connect the Fluke 754 with Fluke Calibration dry-wells and Micro-Baths to automate



Product overview: HART DRYWELL CABLE | An interface cable kit that includes a null modem to connect the Fluke 754 with Fluke Calibration dry-wells and Micro-Baths to automate

Use the HART DRYWELL CABLE to connect the Fluke 754 with these Fluke Calibration temperature sources to automate and document the calibration of temperature sensors and transmitters in the field or at the bench.

- 6102, 7102, and 7103 Micro-Bath Thermometer Calibrators
- 9009 Industrial Dual-Block Thermometer Calibrator
- 9100S and 9102S Handheld Dry-Wells
- 9142, 9143 and 9144 Field Metrology Wells
- 9170, 9171, 9172 and 7173 Metrology Well Calibrators
- 9190A Ultra-Cool Metrology Well

In addition, for more advanced automation at the bench, MET TEMP II Temperature Calibration Software V5.0 is ideal for calibrations requiring multiple temperature sources, generating calibration coefficients and reports,

Ordering information



HART DRYWELL CABLE

An interface cable kit that includes a null modem to connect the Fluke 754 with Fluke Calibration dry-wells and Micro-Baths to automate and document the calibration of temperature sensors and transmitters in the field or at the bench.

Fluke. *Keeping your world up and running.®*

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:

In the U.S.A. (800) 443-5853

In Europe/M-East/Africa

+31 (0)40 267 5100

In Canada (800)-36-FLUKE

From other countries +1 (425) 446-5500

www.fluke.com/en-th

©2025 Fluke Corporation. Specifications subject to change without notice.

04/2025

Modification of this document is not permitted without written permission from Fluke Corporation.