

## TECHNICAL DATA

# 9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well



## Product overview: 9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well

### 9190A Carrying Case

- Carrying case for the 9190A Ultra-Cool Field Metrology Well
- Dent- and shatter-resistant strong resin case
- Foam lined for impact protection
- Handle and wheels for easy transporting

## Specifications: 9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well

### Dimensions

Exterior: (L x W x D) 24.90 in x 23.70 in x 13.10 in (63.25 cm x 60.2 cm x 33.27 cm)

Interior: (L x W x D) 22.50 in x 21.10 in x 11.40 in (57.15 cm x 53.59 cm x 28.96 cm)

**Weight**

With foam: 27 lbs (12.25 kg)

Without foam: 20.1 lbs (9.12 kg)

**Temperature rating**

-10 °F to +210 °F (-23 °C to +99 °C)

## Ordering information



### **9190-CASE**

Carrying Case, 9190A Ultra-Cool Field Metrology Well

---

**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**

PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**

In the U.S.A. (800) 443-5853

In Europe/M-East/Africa

+31 (0)40 267 5100

In Canada (800)-36-FLUKE

From other countries +1 (425) 446-5500

[www.fluke.com/en-th](http://www.fluke.com/en-th)

©2025 Fluke Corporation. Specifications subject to  
change without notice.

04/2025

**Modification of this document is not permitted  
without written permission from Fluke  
Corporation.**