

TECHNICAL DATA

# AC288 Terminal Block Probe with Retractable Probe Tip





## Key features

- Retractable probe tip designed for increased safety, while providing flexibility to reach deep connection points
- Recommended for use with TL224, TL222 or TL221 Test Leads
- 11.5 cm (4.5 in) insulated, flexible shaft
- 1 mm diameter probe tip extends out to 8.4 mm (0.33 in) length
- Retractable probe tip is made with stainless steel
- Safety rated: IEC 61010-031, CAT III 1000 V, CAT IV 600 V
- Operating temperature: -20 °C to 55 °C (-4 °F to 131 °F), 90% RH
- One-year warranty

## Product overview: AC288 Terminal Block Probe with Retractable Probe Tip

Use for safe and secure connections to clamp and screw type terminal blocks.

## Ordering information



**AC288**

---

**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Europe/M-East/Africa  
+31 (0)40 267 5100  
In Canada (800)-36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com/en-th](http://www.fluke.com/en-th)

©2025 Fluke Corporation. Specifications subject to  
change without notice.  
04/2025

**Modification of this document is not permitted  
without written permission from Fluke  
Corporation.**