

TECHNICAL DATA

Fluke TL221 SureGrip™ Test Lead Extenders



Key features

- Extends test leads by 1.5 meters
- Silicone-insulated wire resists heat & cold
- Accepts wide range of Fluke test probes and clips

Product overview: Fluke TL221 SureGrip™ Test Lead Extenders

The Fluke TL221 SureGrip™ Test Lead Extenders includes silicone leads and lead couplers with reinforced strain relief. With 1.5 meters of added length you can reach test points that were previously inaccessible. Rubber over-molded surfaces and finger-hugging curves gives you a comfortable, reliable grip.

Designed for safety

The Fluke TL221 SureGrip™ Test Lead Extenders are CAT III 1000 V, CAT IV 600 V rated.

Compatible with Fluke test probes and clips

TL221 lead extensions are compatible with a wide range of Fluke test probes and clips. Some often-used probe tips include:

- TP175 TwistGuard™ Test Probes
- TP220 SureGrip™ Industrial Test Probes
- AC220 SureGrip™ Alligator Clips
- AC285 SureGrip™ Alligator Clips
- AC280 SureGrip™ Hook Clips
- TP1 SlimReach™ Test Probes
- AC283 SureGrip™ Pincer Clips

Ordering information



Fluke TL221

- One pair (red, black) of silicone insulated leads with straight connectors on both ends
- Reinforced strain relief
- Includes one pair (red, black) of female couplers
- Extends test leads by 1.5 m
- 600 V CAT IV, 1000 V CAT III, 10 A rating. UL listed
- One year warranty

Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Europe/M-East/Africa
+31 (0)40 267 5100
In Canada (800)-36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com/en-th

©2025 Fluke Corporation. Specifications subject to
change without notice.
04/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**