

TECHNICAL DATA

5430 Standard AC/DC Resistors



Key features

- Eight resistance values covering 1 ohm to 10,000 ohms
- Actual resistance within 10 ppm of its nominal value.
- Long-term stability better than 2 ppm/year, with typical performance under 1 ppm.
- Ideal for applications in thermometry and electrical settings, with both AC and DC bridges.

Product overview: 5430 Standard AC/DC Resistors

Six resistors in Fluke Calibration's Model 5430 series cover resistance values from 1 ohm to 10,000 ohms. Each one has an actual resistance within 10 ppm of its nominal value and holds its resistance within 2 ppm per year.

Each resistor comes with a Tinsley certificate on AC performance, traceable to NPL, including calibration uncertainty of 3 ppm. Additionally, Fluke Calibration can provide an optional DC certificate, traceable to NIST and NVLAP accredited, with uncertainty below 1 ppm.

Designed originally by a national lab, Tinsley resistors are bifilar wound to minimize reactance and are filled with oil to minimize both time- and temperature-caused instabilities. AC/DC transfer error at 90 Hz is only 0.1 ppm.

For maintaining your oil resistors, Fluke Calibration provides baths that range from 25- to 155-liter capacity with enough inside shelf space to maintain all your standard resistors. Each of these baths maintains your resistors within 1 mK in the short term (30–60 minutes) and within 5 mK for months at a time.

In our lab, we use both AC and DC [bridges](#) in addition to [Super-Thermometers](#). We calibrate SPRTs in fixed points, and we calibrate reference resistors. We use standard resistors every day, and we understand the value of being able to rely on resistors that won't drift. Tinsley makes the best AC/DC resistors around, and Fluke Calibration makes the best maintenance baths. Ask people who know. Then don't compromise.

Specifications: 5430 Standard AC/DC Resistors

| Specifications | |
|--|--|
| Tolerance | 10 ppm |
| Calibration Uncertainty | AC: 3 ppm (10 kΩ: 4 ppm) DC: 1 ppm (optional) |
| Long-Term Stability | 2 ppm per year |
| Temperature Coefficient | 2 ppm per °C |
| Recommended Current | 1Ω: 100 mA 10Ω: 32 mA 25Ω: 20 mA 100Ω: 10 mA 1 kΩ: 3 mA 10 kΩ: 1 mA |
| Maximum Current | 1Ω: 1 A 10Ω: 320 mA 25Ω: 200 mA 100Ω: 100 mA 1 kΩ: 32 mA 10 kΩ: 10 ma |
| AC/DC Transfer Error (at 90 hz) | 0.1 ppm, typical |

Ordering information



5430-1 Resistor

AC/DC Standard 1 ohm

5430-10 Resistor

AC/DC Standard 10 ohm

5430-25 Resistor

AC/DC Standard 25 ohm

5430-100 Resistor

AC/DC Standard 100 ohm

5430-200 Resistor

AC/DC Standard 200 ohm

5430-400 Resistor

AC/DC Standard 400 ohm

5430-1K Resistor

AC/DC Standard 1 Kohm

5430-10K Resistor

AC/DC Standard 10 Kohm

1960 Cal

DC Standard Resistor

Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Europe/M-East/Africa
+31 (0)40 267 5100
In Canada (800)-36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com/en-th

©2025 Fluke Corporation. Specifications subject to
change without notice.
04/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**