

TECHNICAL DATA

# COMPASS® for molbox™ software



## Key features

- Software assisting molbloc/molbox™ users in calibration.
- Advanced metrology for various gases with real-time measurement.
- Comprehensive calibration system with molbloc/molbox.
- Molbloc/molbox's performance with the versatility of a PC application.

## Product overview: COMPASS® for molbox™ software

### Calibration assistance software for molbloc/molbox™ users

The Fluke Calibration molbloc/molbox is a unique gas flow standard offering state-of-the-art metrology from <1 sccm to several thousand slm with a wide variety of gases and real time measurement capability. COMPASS® for molbox software works with molbloc/molbox to create a full function calibration system. The result is the optimal flow calibration system combining the outstanding performance of molbloc/molbox with the power, versatility and features of a modern PC-based application.

## Features

- Usable on any PC with a 32-bit Windows OS and available COM port.
- Supports both molbox1+ and molbox RFM.
- A true Windows® application following Windows protocol for file management, menu and message formatting, graphics and editing. Other applications can be run without interrupting test execution.
- Complete online Help facility with Tool Tips.
- Customizable user interface with scalable windows.
- Calibrate and test a wide variety of devices including: MFCs, MFMs, rotometers, turbine meters, bubble meters and others.
- Fully automated testing of both analog and digital MFCs.
- Automated flow control support for testing flow measure only devices.
- Flow corrections with automated ambient pressure and temperature entry for density dependent DUTs.
- Log extra data from the DUT during the test with user defined commands.
- Open hardware configuration allows simple integration of third party acquisition, control, and pressure and temperature measurement hardware.
- Sets up and maintains DUT database with unique DUT characteristics, test scripts and histories.
- Process gas editing tool includes complete gas conversion factors for most major MFC manufacturers and automatically calculates conversion factors for missing relationships and blends.
- Produces standard, delimited test data files which easily import into other software programs if desired.
- Test data files stored in user definable directory structure.
- 100% customizable test report generation tool with preformatted templates.
- Extensive on-board plotting function to create a variety of test data plots.

## Specifications: COMPASS® for molbox™ software

Electronic interfaces supported by COMPASS software	
molbox and auxiliary device interfaces	RS-232
	IEEE-488 (National Instruments or CEC interface hardware required)
DUT interfaces	RS-232
	RS 485 (requires RS485-to-RS232 converter)
	IEEE-488 (National Instruments or CEC interface hardware required)
	DVICENET (National Instruments)
Recommended system configuration to run COMPASS for molbox software	
<ul style="list-style-type: none"> <li>• PC with 32-bit Microsoft OS and available COM port</li> <li>• Access to CD drive to load COMPASS for molbox</li> <li>• molbox1 or molbox RFM based mass flow standard</li> </ul>	

# Ordering information



## COMPASS for molbox

COMPASS for molbox flow calibration software

**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Europe/M-East/Africa  
+31 (0)40 267 5100  
In Canada (800)-36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com/en-th](http://www.fluke.com/en-th)

©2025 Fluke Corporation. Specifications subject to  
change without notice.  
04/2025

**Modification of this document is not permitted  
without written permission from Fluke  
Corporation.**