

TECHNICAL DATA

55XXA/COIL 50 | 50-Turn Current Coil



















Product overview: 55XXA/COIL 50 | 50-Turn Current Coil

Optional 50-turn current coil expands workload coverage for calibrating clamp meters and ammeters.

Includes an Accredited 17025 Calibration Certificate Traceable to International Standards with Data.

Specifications: 55XXA/COIL 50 | 50-Turn Current Coil

Specifications	
Number of turns	50
Maximum current	20 A rms, continuous 30.2 A rms, 5 minutes
Maximum voltage, all inputs	30 V to Earth
Minimum inner diameter of clamp jaws	23 mm
Coil ratio	±0.65 %, 3 Hz to 440 Hz. Usable but unspecified at dc and above 440 Hz

Ordering information



55XXA/COIL 50

50-Turn Current Coil

Includes an Accredited 17025 Calibration Certificate Traceable to International Standards with Data



Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2025 Fluke Corporation.
Specifications subject to change without notice.
04/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**