

TECHNICAL DATA

Fluke VPS200-G Voltage Probe Set, Gray 200 MHz (one gray)



Product overview: Fluke VPS200-G Voltage Probe Set, Gray 200 MHz (one gray)

Double insulated voltage probe for ScopeMeter190 series.

Specifications: Fluke VPS200-G Voltage Probe Set, Gray 200 MHz (one gray)

Specifications	
Aenuation	10x
Bandwidth	200 MHz
Max. input voltage	1000 V
Max. voltage to ground	600 V CAT III 1000 V CAT II per IEC / EN61010-031
Input resistance	10 Mohm
Input capacitance	14 pF



Compensation range	10 to 22 pF
Cable length	1.2m
Warranty	1 Year
Specifications apply when the probe is connected to Fluke 190 Series Scopemeter.	



Ordering information



Fluke VPS200 G

Voltage Probe Set, Gray 200 MHz (one gray)

Each probe set includes:

- 600 V CAT III / 1000 V CAT II rated:
 - o 10:1 Voltage Probe
 - o Hook Clip for Probe Tip, 4-mm Test Probe for Probe
 - o Ground Lead with Hook Clip
 - o Ground Lead with Mini Alligator
- The red probe set also includes a 30 V CAT II rated Ground Spring for Probe Tip



$\textbf{Fluke}. \ \textit{Keeping your world up and running.} \\ \textbf{@}$

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call: In the U.S.A. (800) 443-5853

In Canada (800) 36-FLUKE From other countries +1 (425) 446-5500 www.fluke.com ©2025 Fluke Corporation.

Specifications subject to change without notice.

04/2025

Modification of this document is not permitted without written permission from Fluke Corporation.