

TECHNICAL DATA

2566 | Thermocouple Scanner Module, 12-channel



Product overview: 2566 | Thermocouple Scanner Module, 12channel

This module has 12 channels and reads K, J, T, S, R, B, E, and N thermocouples. (Support for C and U type thermocouples is available. Download the application note <u>Using Fluke Calibration Readouts with Tungsten-Rhenium and other Thermocouples</u> ») Each channel can be set to read a different type of thermocouple. All temperature readings are performed in exactly the same manner as with the 2565 module.

The connectors on the scanner module are special dual connectors that accept both the common miniature and standard thermocouple connectors. If you want to use screw terminals, use the appropriately- sized connector with the hood removed.



Ordering information



2566

Thermocouple Scanner Module, 12-channel



$\textbf{Fluke}. \ \textit{Keeping your world up and running.} \\ \textbf{@}$

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:

In the U.S.A. (800) 443-5853 In Canada (800) 36-FLUKE From other countries +1 (425) 446-5500

www.fluke.com

©2025 Fluke Corporation.

 $\label{thm:continuous} Specifications \ subject \ to \ change \ without \ notice.$

04/2025

Modification of this document is not permitted without written permission from Fluke Corporation.