

TECHNICAL DATA

Fluke TL2X4W-PTII 2x4 Wire Ohms Test Lead 2 mm Probe Tip



Key features

- Perform 4-wire measurements with only two test leads
- Two conductors per lead (one source and one measure)
- Excellent resolution and accuracy

Specifications: Fluke TL2X4W-PTII 2x4 Wire Ohms Test Lead 2 mm Probe Tip

Specifications		
Maximum voltage between test lead and ground	1000 V	
Maximum transient overvoltage and input voltage combined	1000 V	
Maximum current	500 mA	
Temperature	Operating:	0 °C to 55 °C < 90% relative humidity
	Storage:	-40 °C to 170 °C

Altitude	2000 m
Safety	Complies with EN/IED 61010-031 and CAN/CSA C22.2 No. 61010-1-04 for Measurement Category 1 1000 V

Ordering information



Fluke TL2X4W-PTII

2x4 Wire Ohms Test Lead 2 mm Probe Tip

Fluke. *Keeping your world up and running.®*

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:

In the U.S.A. (800) 443-5853

In Canada (800) 36-FLUKE

From other countries +1 (425) 446-5500

www.fluke.com

©2025 Fluke Corporation.

Specifications subject to change without notice.

04/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**