

TECHNICAL DATA

Fluke BC430 Line Voltage Adapter/Battery Charger



Key features

- Mains (Line Voltage): switchable 115 V \pm 15% or 230 V \pm 15%
- Equipped with a male receptacle plug that must be connected to a line cord/adapter appropriate for local use. (Line cord/adapter not included)

Product overview: Fluke BC430 Line Voltage Adapter/Battery Charger

Provides power cord operation and charging for Fluke 430 Series Power Quality Analyzers.

Specifications: Fluke BC430 Line Voltage Adapter/Battery Charger

Specifications	
Frequency (all versions)	5060 Hz ± 10%
Output voltage	17.8 V DC
Output power	15 W



Power consumption	23.7 VA
Max. voltage to ground	600 V CAT IV per IEC 1010-1



Ordering information



Fluke BC430

BC430 Line Voltage Adapter/Battery Charger



Fluke. Keeping your world up and running.®

Fluke Europe B.V. P.O. Box 1186 5602 BD Eindhoven The Netherlands www.fluke.com/en ©2025 Fluke Corporation. All rights reserved. Data subject to alteration without notice. 04/2025

Modification of this document is not permitted without written permission from Fluke Corporation. For more information call: In Middle East/Africa +31 (0)40 267 5100