

TECHNICAL DATA

# Fluke VPS100-R 10:1 Voltage Probe Red 100 MHz (one red)



## Key features

For ScopeMeter 90 Series, replaces PM8918 probe series.

- Double insulated voltage probe

## Specifications: Fluke VPS100-R 10:1 Voltage Probe Red 100 MHz (one red)

General Specifications	
Aenuation	10x
Bandwidth	100 MHz
Max. input voltage	600 V CAT III, 1000 V CAT II per IEC / EN61010-2-031
Max. Voltage to ground	600 V CAT III, 1000 V CAT II per IEC / EN61010-2-031
Input Resistance	10 Mohm
Input Capacitance	16 pF



Compensation range	10 to 35 pF
Cable Length	1.2 m
BB120 Shielded Banana to BNC Adapter is required to adapt to ScopeMeter 120 Series shielded banana jack inputs.	

## Ordering information



### Fluke VPS100 R

10:1 Voltage Probe Red 100 MHz (one red)

Each probe set includes:

- 600 V CAT III
- 10:1 Voltage Probe (1 red)
- Hook Clip for Probe Tip (1 red)
- 4-mm Test Probe for Probe (1 red)
- Ground Lead with Hook Clip (1 red)
- Ground Lead with Mini Alligator (1 black)

**Fluke.** *Keeping your world up and running.®*

**Fluke Europe B.V.**

P.O. Box 1186  
5602 BD Eindhoven  
The Netherlands  
[www.fluke.com/en](http://www.fluke.com/en)

©2025 Fluke Corporation. All rights reserved.  
Data subject to alteration without notice.  
04/2025

**For more information call:**

In Middle East/Africa  
+31 (0)40 267 5100

**Modification of this document is not permitted  
without written permission from Fluke  
Corporation.**