

TECHNICAL DATA

## 5013-1L | Silicone Oil, Type 200.20, 1 liter (0.26 gal)



### Product overview: 5013-1L | Silicone Oil, Type 200.20, 1 liter (0.26 gal)

Silicone oil is used as a calibration media in temperature controlled baths. Different types of silicone oil are chosen for specific temperature ranges based on their viscosity at those temperatures. They have good thermal characteristics and low flammability.

- Silicone oil bath fluid type 200.20

- Usable range: 10 °C to 230 °C
- FlashPoint: 232 °C

Atmospheric pressure affects the usable range of some fluids. The temperatures quoted are at sea level.

Flash point is the temperature at which a vapor (not the fluid) will ignite if exposed to an open flame. When the flame is removed, the vapor will stop burning. (Open cup method).

## Ordering information



### **5013-3.8L**

Silicone Oil, Type 200.20, 1 liter (0.26 gal)

**Fluke.** *Keeping your world up and running.®*

**Fluke Europe B.V.**

P.O. Box 1186  
5602 BD Eindhoven  
The Netherlands  
[www.fluke.com/en](http://www.fluke.com/en)

©2025 Fluke Corporation. All rights reserved.  
Data subject to alteration without notice.  
03/2025

**For more information call:**

In Middle East/Africa  
+31 (0)40 267 5100

**Modification of this document is not permitted  
without written permission from Fluke  
Corporation.**