

Datos técnicos

9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well



Descripción general del producto: 9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well

9190A Carrying Case

- Carrying case for the 9190A Ultra-Cool Field Metrology Well
- Dent- and shatter-resistant strong resin case
- Foam lined for impact protection
- Handle and wheels for easy transporting

Especificaciones: 9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well

Dimensions

Exterior: (L x W x D) 24.90 in x 23.70 in x 13.10 in (63.25 cm x 60.2 cm x 33.27 cm)
Interior: (L x W x D) 22.50 in x 21.10 in x 11.40 in (57.15 cm x 53.59 cm x 28.96 cm)

Weight

With foam: 27 lbs (12.25 kg)

Without foam: 20.1 lbs (9.12 kg)

Temperature rating

-10 °F to +210 °F (-23 °C to +99 °C)

Modelos



9190-CASE

Carrying Case, 9190A Ultra-Cool Field Metrology Well

Fluke. *Manteniendo su mundo en marcha.*

Fluke Corporation
Everett, WA 98206 EE.UU.

Para obtener información adicional En EE. UU.
(800) 443-5853

En Europa/Medio Oriente/África
+31 (0)40 267 5100

En Canadá (800)-36-FLUKE
www.fluke.com

Latin America
Tel: +1 (425) 446-5500
www.fluke.com/es-bo

©2025 Fluke Corporation. Reservados todos los derechos. Impreso en los Países Bajos. Información sujeta a modificación sin previo aviso.
04/2025

No está permitido modificar este documento sin autorización por escrito de Fluke Corporation.