

Tekniset tiedot

Fluke 87V/E2 Combo teollisuuspaketti





Tärkeimmät ominaisuudet

All functionality of the 87V Industrial Digital Multimeter, plus:

- Fully insulated 3 mm exposed metal test probes for electricians working in high energy environments
- C35 Soft Carrying Case holds meter, test leads and other accessories
- TPAK magnetic hanging strap lets you attach the meter to any ferrous surface, such as cabinets and iron pipes.

Tuotekatsaus: Fluke 87V/E2 Combo teollisuuspaketti

Uusi Combo-paketti perustuu Fluke 87V -mittariin ja sen sisältämien erikoislisävarusteiden ansiosta teollisuuden vianetsintä käy entistä tuottavammaksi. Paketin oston yhteydessä säästät lisävarusteiden hinnassa yli 15 % verrattuna siihen, jos ostaisit lisävarusteet erikseen.

Tekniset tiedot: Fluke 87V/E2 Combo teollisuuspaketti

Specifications		
Voltage DC	Maximum Voltage	1000 V
	Accuracy	$\pm(0.05\% + 1)$
	Maximum Resolution	10 μ V
Voltage AC	Maximum Voltage	1000 V
	Accuracy	$\pm(0.7\% + 2)$ True RMS
	AC Bandwidth	20 kHz with low pass filter; 3 db @ 1 kHz
	Maximum Resolution	0.1 mV
Current DC	Maximum Amps	10 A (20 A for 30 seconds maximum)
	Amps Accuracy	$\pm(0.2\% + 2)$
	Maximum Resolution	0.01 μ A
Current AC	Maximum Amps	10 A (20 A for 30 seconds maximum)
	Amps Accuracy	$\pm(1.0\% + 2)$ True RMS
	Maximum Resolution	0.1 μ A
Resistance	Maximum Resistance	50 M Ω
	Accuracy	$\pm(0.2\% + 1)$
	Maximum Resolution	0.1 Ω
Capacitance	Maximum Capacitance	9,999 μ F
	Accuracy	$\pm(1\% + 2)$
	Maximum Resolution	0.01 nF

Frequency	Maximum Frequency	200 kHz
	Accuracy	±(0.005% + 1)
	Maximum Resolution	0.01 Hz
Duty Cycle	Maximum Duty Cycle	99.9%
	Accuracy	±(0.2% per khz +0.1%)
	Maximum Resolution	0.1%
Temperature Measurement	-200.0°C - 1090°C -328.0°F - 1994.0°F excluding probe	
80 BK Temperature Probe	-40.0°C - 260°C -40.0°F - 500°F, 2.2°C or 2% whichever is greater	
Conductance	Maximum Conductance	60.00 nS
	Accuracy	±(1.0% + 10)
	Maximum Resolution	0.01 nS
Diode	Range	3 V
	Resolution	1 mV
	Accuracy	±(2% + 1)
Duty Cycle Range	Accuracy	Within ±(02% per kHz +0.1%)
Environmental Specifications		
Operating Temperature	-20°C to +55°C	
Storage Temperature	-40°C to +60°C	
Humidity (Without Condensation)	0% - 90% (0°C - 35°C) 0% - 70% (35°C - 55°C)	
Operating Altitude	2000 m	
Safety Specifications		
Overvoltage category	EN 61010-1 to 1000 V CAT III, 600V CAT IV	
Agency Approvals	UL, CSA, TÜV, VDE listed	
Mechanical and General Specifications		
Size	201 x 98 x 52 mm (with holster)	
Weight	355 g 624 g - with holster	
Display	Digital	6000 counts updates 4/sec. 19,999 counts in high-resolution mode
	Analog	32 segments, updates 40/sec.
	Frequency	19,999 counts, updates 3/sec at > 10 Hz
Warranty	Lifetime	
Baery Life	Alkaline	~400 hours typical, without backlight
Shock	1 Meter drop per IEC 61010-1:2001	

Vibration	Per MIL-PRF-28800 for a Class 2 instrument
-----------	--

Mallit



Fluke 87V/E2 Kit

Yleismittari

Vakiovarusteet:

- 87V-yleismittari
- TL224-silikonimittajohdot
- suuret AC220-hauenleuat
- TP238-mittauskärjet
- magneetti ja hihna
- 80BK lämpötila-anturi
- suojakotelo
- 9 V:n paristo (asennettu valmiiksi)

Fluke. *Keeping your world up and running.®*

Fluke Finland Oy
Teknobulevardi 3-5
01530 VANTAA
Puh.: 0800 111 862
E-mail: cs.fi@fluke.com
www.fluke.fi

©2025 Fluke Corporation. Kaikki oikeudet
pidätetään. Oikeudet muutoksiin ilman
ennakkoilmoitusta pidätetään.
04/2025

**Tätä asiakirjaa ei saa muokata ilman Fluke
Corporationin kirjallista lupaa.**