

Fiche technique

## 9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well



### Présentation du produit: 9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well

9190A Carrying Case

- Carrying case for the 9190A Ultra-Cool Field Metrology Well
- Dent- and shatter-resistant strong resin case
- Foam lined for impact protection
- Handle and wheels for easy transporting

### Spécifications: 9190-CASE | Carrying Case, 9190A Ultra-Cool Field Metrology Well

#### Dimensions

Exterior: (L x W x D) 24.90 in x 23.70 in x 13.10 in (63.25 cm x 60.2 cm x 33.27 cm)

Interior: (L x W x D) 22.50 in x 21.10 in x 11.40 in (57.15 cm x 53.59 cm x 28.96 cm)

**Weight**

With foam: 27 lbs (12.25 kg)

Without foam: 20.1 lbs (9.12 kg)

**Temperature rating**

-10 °F to +210 °F (-23 °C to +99 °C)

## Modèles



### **9190-CASE**

Carrying Case, 9190A Ultra-Cool Field Metrology Well

---

*Soyez à la pointe du progrès avec Fluke.*

**Fluke (Switzerland) GmbH**  
Industrial Division  
Hardstrasse 20  
CH-8303 Bassersdorf  
Tel: +41 (0) 44 580 7504  
E-mail: roc.switzerland@fluke.com  
www.fluke.com/fr-ch

©2025 Fluke Corporation. Tous droits réservés.  
Informations modifiables sans préavis.  
04/2025

**La modification de ce document est interdite sans  
l'autorisation écrite de Fluke Corporation.**