

1586-2586/C | High-Capacity Module without Relay Card, Accredited Calibration



Présentation du produit: 1586-2586/C | High-Capacity Module without Relay Card, Accredited Calibration

If you want to configure the 1586A yourself to work with the 1586-2586 High-Capacity Module, you will need a relay card. However, if you already have a slot in the back panel of the 1586A configured for use with the 1586-2586, then you don't need another relay card. You can simply slide the 1586-2586 High-Capacity Module into the preconfigured slot and begin taking measurements. The 1586-2586 High-Capacity Module is designed with universal input channels



to measure temperature, resistance, dc voltage, and dc current for data acquisition applications where channel count and scan speed are important.

Spécifications: 1586-2586/C | High-Capacity Module without Relay Card, Accredited Calibration

Specifications	
Maximum Input	50 V
Offset Voltage	<2 µV
3-Wire Inteal Resistance Mismatch	<50 mΩ
Basic CJC Accuracy	0.6 °C

Modèles



1586-2586/C

High-Capacity Module without Relay Card, Accredited Calibration

Soyez à la pointe du progrès avec Fluke.

Fluke (Switzerland) GmbH
Industrial Division
Hardstrasse 20
CH-8303 Bassersdorf
Tel: +41 (0) 44 580 7504
E-mail: roc.switzerland@fluke.com
www.fluke.com/fr-ch

©2025 Fluke Corporation. Tous droits réservés.
Informations modifiables sans préavis.
04/2025

**La modification de ce document est interdite sans
l'autorisation écrite de Fluke Corporation.**