

Data teknis

Fluke i410 AC/DC Current Clamp



Fitur utama

- Battery-powered Hall-effect probe measures 1A to 400 A
- 1mV/Amp output guarantees easy reading on your meter
- Take accurate current readings without breaking the circuit
- Maximum conductor Ø 32 mm
- CAT III 600 V safety rating
- Also available with softcase for DMM and clamp (i410 kit)
- One year warranty

Ikhtisar Produk: Fluke i410 AC/DC Current Clamp

The Fluke i410 AC/DC current clamp expands the functionality of digital multimeters and measures up to 400 amps for both AC and DC current. The Large clamp claw gives you access to difficult to reach areas. The kit includes a handy carrying case.

Spesifikasi: Fluke i410 AC/DC Current Clamp

| Specifications | |
|---------------------------------------|---|
| Measurement type | Hall sensor |
| Nominal current range | 400 A, AC/DC |
| Continuous current range | 1 A - 400 A AC/DC |
| Maximum non-destructive current | 400 A |
| Lowest measureable current | 0.5 A |
| Basic accuracy | 3.5% + 0.5 A (% reading + floorspec) |
| Useable frequency | DC - 3 kHz |
| Output level(s) | 1 mV/A |
| Zero error adjustment | Yes |
| Safety Specifications | |
| Safety | CAT III, 600 V |
| Maximum voltage | 600 V |
| Mechanical and General Specifications | |
| Warranty | 1 year |
| Baery life | 9 V, 60 h |
| Maximum conductor diameter | 30 mm 2 x 25 mm |
| Output cable length | 1.6 m |



| | |
|-----------------------|-----|
| Shrouded banana plugs | Yes |
|-----------------------|-----|

Model



i410

AC/DC Current Clamp

Fluke. *Memastikan aktivitas Anda terus berjalan dan beroperasi.*

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:

In the U.S.A. (800) 443-5853

In Europe/M-East/Africa

+31 (0)40 267 5100

In Canada (800)-36-FLUKE

From other countries +1 (425) 446-5500

www.fluke.com

BUT. FLUKE SOUTH EAST ASIA PTE LTD

Menera Satu Sentra Kelapa Gading #06-05

Jl. Bulevar Kelapa Gading Kav. LA# No. 1

Summarecon Kelapa Gading

Jakarta Utara 14240

Indonesia

Tel: +62 21 2938 5922

Email: info.asean@fluke.com

www.fluke.com/id

©2025 Fluke Corporation. Specifications subject to change without notice.

03/2025

Modification of this document is not permitted without written permission from Fluke Corporation.