

Data teknis

VPS212-G - Voltage Probe Set, 10:1, one grey



Ikhtisar Produk: VPS212-G - Voltage Probe Set, 10:1, one grey

Double insulated voltage probe for ScopeMeter 190 series.

Each probe set includes:

- 600 V CAT III / 1000 V CAT II rated 10:1 Voltage Probe
- Hook Clip for Probe Tip
- Ground Lead with Mini Alligator
- Insulation Sleeve
- 30 V CAT II rated Ground Spring for Probe Tip

Specification:

- Attenuation: 10x
- Bandwidth: 200 MHz
- Max. Input Voltage 1000 V CAT II or 600 V CAT III
- Max. Voltage to ground: 1000 V CAT II or 600 V CAT III per IEC / EN61010-031
- Input Resistance: 10 M Ω
- Input Capacitance: 18 pF
- Compensation range: 10 to 30 pF
- Cable Length: 2.5 m

Spesifikasi: VPS212-G - Voltage Probe Set, 10:1, one grey

Specification	
Aenuation	10x
Bandwidth	200 MHz
Max. input voltage	1000 V CAT II or 600 V CAT III
Max. voltage to ground	1000 V CAT II or 600 V CAT III per IEC / EN61010-031
Input resistance	10 MΩ
Input capacitance	18 pF
Compensation range	10 to 30 pF
Cable length	2.5 m

Fluke. *Memastikan aktivitas Anda terus berjalan dan beroperasi.*

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:

In the U.S.A. (800) 443-5853

In Europe/M-East/Africa

+31 (0)40 267 5100

In Canada (800)-36-FLUKE

From other countries +1 (425) 446-5500

www.fluke.com

BUT. FLUKE SOUTH EAST ASIA PTE LTD

Menera Satu Sentra Kelapa Gading #06-05

Jl. Bulevar Kelapa Gading Kav. LA# No. 1

Summarecon Kelapa Gading

Jakarta Utara 14240

Indonesia

Tel: +62 21 2938 5922

Email: info.asean@fluke.com

www.fluke.com/id

©2025 Fluke Corporation. Specifications subject to change without notice.

03/2025

Modification of this document is not permitted without written permission from Fluke Corporation.