

Fluke 179/61 Industrial Multimeter and Infrared Thermometer Combo Kit



Ikhtisar Produk: Fluke 179/61 Industrial Multimeter and Infrared Thermometer Combo Kit

Multimeter dan Infrared Thermometer Combo Kit

Dibuat untuk pemeliharaan industri, HVAC (pemanasan, ventilasi, dan pendingin udara), dan fasilitas. Multimeter true-rms yang kuat dengan termometer bawaan untuk memecahkan masalah listrik dan elektromekanis ditambah termometer inframerah terpadu laser tanpa kontak untuk mengukur putaran atau peralatan yang dialiri listrik, dikemas dalam kotak pembawa yang tahan lama.

Spesifikasi: Fluke 179/61 Industrial Multimeter and Infrared Thermometer Combo Kit

Fluke 179 Digital Multimeter

Specifications

Voltage DC	Accuracy¹	$\pm(0.09\% + 2)$
	Max. resolution	0.1 mV
	Maximum	1000 V
Voltage AC	Accuracy¹	$\pm(1.0\% + 3)$
	Max. resolution	0.1 mV
	Maximum	1000 V
Current DC	Accuracy¹	$\pm(1.0\% + 3)$
	Max. resolution	0.01 mA
	Maximum	10 A
Current AC	Accuracy¹	$\pm(1.5\% + 3)$
	Max. resolution	0.01 mA
	Maximum	10 A
Resistance	Accuracy¹	$\pm(0.9\% + 1)$
	Max. resolution	0.1 Ω
	Maximum	50 M Ω
Capacitance	Accuracy¹	$\pm(1.2\% + 2)$
	Max. resolution	1 nF
	Maximum	10,000 μ F
Frequency	Accuracy¹	$\pm(0.1\% + 1)$
	Max. resolution	0.01 Hz
	Maximum	100 kHz
Temperature	Accuracy¹	$\pm(1.0\% + 10)$
	Max. resolution	0.1°C
	Range	-40°C/400°C

1. Accuracies are best accuracies for each function

Environmental Specifications

Operating temperature	-10°C to +50°C
Storage temperature	-30°C to +60°C
Humidity (without condensation)	0% - 90% (0°C - 35°C) 0% - 70% (35°C - 50°C)

Safety Specifications

Overvoltage category	EN 61010-1 to 1000 V CAT III EN 61010-1 to 600 V CAT IV
Agency approvals	UL, CSA, TÜV listed and VDE Pending

Mechanical and General Specifications

Size	43 x 90 x 185 mm
------	------------------

Weight	420 g
Warranty	Lifetime
Baery life	Alkaline ~200 hours typical, without backlight

Fluke 61 IR Thermometer

Specifications		
Backlit display for use in poorly lit areas	Yes	
Holds temperature readings	Yes	
Range	-18 to 275°C (-0 to 525°F)	
MIN/MAX/AVG	N/A	
Datalogging	N/A	
Distance to spot ratio	8:1	
Hi-Lo alarm	N/A	
Optional RTD probe (contact temperature measurement)	N/A	
Emissivity	Fixed at 0.95	
Measurement accuracy	-18°C (0°F) to -1°C (30°F)	±3°C (5°F)
	above -1°C (30°F) to 275°C (525°F)	±2% of reading or 2°C (3.5°F)
	(With the instrument stable between 23-25°C)	

Model



Fluke 179/61 Kit

Fluke 179/61 Industrial Multimeter and Infrared Thermometer Combo Kit

Barang yang Disertakan

- Kotak Aksesori dan Pengukur Keras C800
 - Multimeter True RMS Fluke 179
 - Termometer Inframerah Fluke 61/A
-

Fluke. *Memastikan aktivitas Anda terus berjalan dan beroperasi.*

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:

In the U.S.A. (800) 443-5853

In Europe/M-East/Africa

+31 (0)40 267 5100

In Canada (800)-36-FLUKE

From other countries +1 (425) 446-5500

www.fluke.com

BUT. FLUKE SOUTH EAST ASIA PTE LTD

Menera Satu Sentra Kelapa Gading #06-05

Jl. Bulevar Kelapa Gading Kav. LA# No. 1

Summarecon Kelapa Gading

Jakarta Utara 14240

Indonesia

Tel: +62 21 2938 5922

Email: info.asean@fluke.com

www.fluke.com/id

©2025 Fluke Corporation. Specifications subject to change without notice.

04/2025

Modification of this document is not permitted without written permission from Fluke Corporation.