

テクニカル・データ

2626-H | スペア・センサー、高確度



製品概要: 2626-H | スペア・センサー、高確度

One of the potential advantages of a digital thermo-hygrometer is that instead of sending the entire unit out for calibration, you can simply swap sensors and send only the sensors due for calibration out of the lab. The 1620A “DewK” Thermo-Hygrometer allows you to swap sensors without shutting it down or discontinuing your other readings.

Smart sensors make this possible because all of the calibration information is contained inside the sensor. Your costs are reduced because the 1620A never needs to be calibrated since it is only a display. Spare sensors like the 2626-S are less expensive to store, ship and recalibrate than an extra chart recorder.

The 2626-H is a spare high-accuracy smart sensor for all models of the DewK Thermo-Hygrometer.

仕様: 2626-H | スペア・センサー、高確度

Size (L x Dia): 79 mm x 19 mm (3.1 x 0.75 in)

モデル



2626-H

スペア・センサー、高確度

Fluke. 動き続ける世界を支える

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A./div>
お問い合わせ先: ©2025 Fluke
フルーク Corporation.
特約店営業部 仕様は、予告なく変更され
TEL : 03-6714-3114 る場合があります。
www.fluke.com/jp/ 04/2025

世界で最も信頼されている
ツール